



Products for Your Home

 [SITE SEARCH](#)
[HOME](#)[PRODUCTS](#)[DESIGN WITH LIGHT](#)[COUPONS / SPECIAL OFFERS](#)[Where to Buy](#) | [FAQs](#) | [Contact Us](#)[Home](#) > [Products](#) > [F20T12/BL](#) > 10244**10244 – F20T12/BL 6PK**

GE T12 - Blacklight

[Print](#)[Features & Photos](#)[Technical Specifications](#)[WHERE TO BUY](#)[View Larger](#)**PRODUCT INFORMATION**

Base	Medium Bi-Pin (G13)
Product Code	10244
Description	F20T12/BL 6PK
UPC	043168953078

GENERAL CHARACTERISTICS

Lamp type	Linear Fluorescent - Straight Linear
Bulb	T12
Base	Medium Bi-Pin (G13)
Bulb Finish	Blacklight/blacklight blue
Wattage	20
Voltage	57
Rated Life	9000 hrs
Rated Life (instant start) @ Time	9000 h @ 3 h
Starting Temperature (MIN)	10 °C (50 °F)
Additional Info	TCLP compliant
Primary Application	Blacklight

ELECTRICAL CHARACTERISTICS

Open Circuit Voltage (rapid start) (MAX)	220 V
Open Circuit Voltage (rapid start) Min @ Temperature	157 V @ 10 °C
Cathode Resistance Ratio - Rh/Rc (MAX)	6.5
Preheat Voltage (MIN)	4 V

DIMENSIONS

Maximum Overall Length (MOL)	24.0000 in (609.6 mm)
Bulb Diameter (DIA)	1.500 in (38.1 mm)
Bulb Diameter (DIA) (MAX)	1.590 in (40.3 mm)
Face to End of Opposing Pin (B) (MAX)	23.500 in (596.9 mm)

 **CAUTIONS & WARNINGS**

[See list of cautions & warnings](#)

[Home](#) | [Products](#) | [Design with Light](#) | [Coupons / Special Offers](#) | [Where to Buy](#) | [FAQs](#) | [Contact Us](#) | [GE Around the World](#) | [Site Map](#)
[Commercial Products & Solutions](#) | [Press Room](#) | [Corporate](#) | [Investor Information](#) | [Privacy Policy](#) | [Accessibility Statement](#) | [Terms of Use](#)

Copyright General Electric Company 1997- 2008