

[Return to search](#)[Print Page](#)

**Product Number:** 29505  
**Order Abbreviation:** F96T12/CW/SS/ECO  
**General Description:** 60W, 96" MOL, T12 instant start Slimline SUPER SAVER fluorescent lamp, Cool White phosphor, 4200K color temperature, 60 CRI, ECOLOGIC, replaces F96T12 IS lamps

#### Product Information

Abbrev. With Packaging Info.	F96T12CWSSECO 15/CS 1/SKU
Actual Length (in)	94
Actual Length (mm)	2387.6
Average Rated Life (hr)	12000
Base	Single Pin
Bulb	T12
Color Rendering Index (CRI)	60
Color Temperature/CCT (K)	4200
Diameter (in)	1.59
Diameter (mm)	40.46
Family Brand Name	Ecologic, SuperSaver
Industry Standards	ANSI C78.81 - 2001
Initial Lumens at 25C	5300
Mean Lumens at 25C	4664
Nominal Length (in)	96
Nominal Wattage (W)	60.00

#### Additional Product Information

[Product Documents, Graphs, and Images](#)

[Compatible Ballast](#)

[Packaging Information](#)



#### Footnotes

- Recommended for use on one or two lamp high power factor, lead, instant-start, indoor ballasts that meet ANSI standards. Not intended for use: (1) at lamp ambient temperatures below 60 degrees F or in drafty locations, (2) on low power factor ballasts,

(3) reduced current/reduced light output ballasts, (4) dimming ballasts, or (5) on inverter operated emergency lighting systems unless any of the above equipment is specifically listed for use with 32 watt or 60 watt lamps.

- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified conditions and with ballast meeting ANSI specifications. If burning cycle is increased, there will be a corresponding increase in the average hours life.
- SYLVANIA ECOLOGIC fluorescent lamps are designed to pass the Federal Toxic Characteristic Leaching Procedure (TCLP) criteria for classification as non-hazardous waste in most states. TCLP test results are available upon request. Lamp disposal regulations may vary, check your local & state regulations. For more information, please visit [www.lamprecycle.org](http://www.lamprecycle.org)
- Average life rating at 12 hours operation per start is 18,000 hours.

[Print Page](#)