

[Return to search](#)[Print Page](#)

**Product Number:** 24065  
**Order Abbreviation:** FB34/D35/6/SS (FB40/D35/SS)  
**General Description:** 34W, T12 Curvalume rapid start SUPER SAVER fluorescent lamp, 6" leg spacing, Designer rare earth phosphor, 3500K color temperature, 70 CRI

#### Product Information

Abbrev. With Packaging Info.	FB34D356SS (FB40D35SS) 12/CS 1/SKU
Actual Length (in)	22.6
Actual Length (mm)	574.0
Average Rated Life (hr)	18000
Base	Medium Bipin
Bulb	T12
Color Rendering Index (CRI)	70
Color Temperature/CCT (K)	3500
Diameter (in)	1.59
Diameter (mm)	40.4
Family Brand Name	Designer, SuperSaver
Industry Standards	ANSI C78.901 - 2001
Initial Lumens at 25C	2730
Mean Lumens at 25C	2457
Nominal Length (in)	22.5
Nominal Wattage (W)	34.00

#### Additional Product Information

[Product Documents, Graphs, and Images](#)

[Compatible Ballast](#)

[Packaging Information](#)



#### Footnotes

- Recommended for use on one or two lamp 40 watt rapid start, high power factor, lead, indoor ballasts that meet ANSI standards. Not intended for use: (1) at lamp ambient temperatures below 60 degrees F or in drafty locations, (2) on low power factor ballasts, (3) reduced current/reduced light output ballasts, (4) dimming ballasts, or (5) on inverter operated emergency lighting systems unless any of the above equipment is specifically listed for use with 34 watt lamps.
- Average rated life is measured at 3 hours per start on 2-lamp, rapid start magnetic ballasts per IES recommended practice. Lamp life on single-lamp rapid start ballasts may be reduced.
- Approximate initial lumens after 100 hours operation.

- The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified conditions and with ballast meeting ANSI specifications. If burning cycle is increased, there will be a corresponding increase in the average hours life.

[Print Page](#)