



Commercial Products & Solutions

 [SITE SEARCH](#)
[HOME](#)[PRODUCTS](#)[EDUCATION / RESOURCES](#)[LIGHTING APPLICATIONS](#)[Where to Buy](#) | [FAQs](#) | [Contact Us](#) | [EliteNet](#)[Products](#) > 41457**41457 – FLE29QBX/DV/827**

GE Soft White Biax® T4 - Facilities; Retail Display; Hospitality; Office; Restaurant



- Up to 75% energy savings One piece unit screws directly into incandescent sockets

- Super long life


High Color Rendering
Energy Savings

UL Listed


**GENERAL CHARACTERISTICS**

Lamp type	Compact Fluorescent - Self-Ballasted
Bulb	T4
Base	Medium Screw (E26)
Wattage	29
Equivalent Wattage	100 W
Rated Life	10000 hrs
Starting Temperature (MIN)	-23 °C (-9 °F)
Total Harmonic Distortion (THD)	170 %
Picograms of Mercury	267 picograms
Additional Info	Dimmable on standard incandescent dimmer.
Primary Application	Standard; Facilities; Retail Display; Hospitality; Office; Restaurant

Bulb



Base

[View Larger](#)**ADDITIONAL RESOURCES****Catalogs****Testimonials****Brochures**

Product Brochures

- [Compact Fluorescent Lamps](#)
 - [Color](#)
- Application/Segment Brochures
- [Restaurant Lighting](#)
 - [Healthcare Lighting](#)
 - [Contractor Lighting](#)

Disposal Policies & Recycling Information**PHOTOMETRIC CHARACTERISTICS**

Initial Lumens	1750
Mean Lumens	1500
Nominal Initial Lumens per Watt	60
Color Temperature	2700 K
Color Rendering Index (CRI)	82

ELECTRICAL CHARACTERISTICS

Input Voltage	120 V
Power Factor	0.6

DIMENSIONS

Maximum Overall Length (MOL)	6.3000 in (160.0 mm)
Nominal Length	6.300 in (160.0 mm)

PRODUCT INFORMATION

Product Code	41457
Description	FLE29QBX/DV/827
Standard Package	Case
Standard Package GTIN	10043168414576
Standard Package Quantity	6
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	6
UPC	043168414579

⚠ CAUTIONS & WARNINGS

[See list of cautions & warnings.](#)

NOTES

- Amalgam product experience stable brightness over a wider temperature range and in various operating positions.
 - Best performance if operated base up and at 77 degrees F (25C) ambient temperature.
 - Fluorescent lamp lumens decline during life
 - Lumens on one piece self ballasted lamp systems are measured base up.
 - Most one piece self ballasted lamps for incandescent sockets and plug-in lamps with screw-in adapters do not work with clip-on shades
 - Use only on 120V 60 Hz circuits. Do not use in wet locations.
-

[Return To Top](#)

[Home](#) | [Products](#) | [EliteNet](#) | [Education/Resources](#) | [Lighting Applications](#) | [Where to Buy](#) | [FAQs](#) | [Contact Us](#) | [Site Map](#)
[Products for Your Home](#) | [Press Room](#) | [Corporate](#) | [Investor Information](#) | [Privacy Policy](#) | [Accessibility Statement](#) | [Terms of Use](#)

Copyright General Electric Company 1997-2008