



ProLume®  
 < T3 Mini-Spirals

## ProLume® T3 Mini-Spirals



### Energy Efficient

- Maximum light distribution achieved through compact design
- Save up to 80% in energy costs compared to incandescent lamps
- Tri-phosphor coating enhances lumen efficacy and color rendering, 82 CRI

### Technical Data

- E26 base, GU24 base
- Electronic instant start ballast
- 120 volt, 60Hz
- Minimum starting temperature -10°F
- Nickel-plated brass base

### Broad Assortment

- Dimmable 14 and 24 watts
- 3-Way 13/20/25 watts, 2700 and 4100K
- 7 to 42 watts, 2700, 3500, 4100, 5000 and 6500K
- Colors available in 11 and 15 watt
- Black-Light Blue available in 15 watt
- GU24 18, 23 and 26 watts, 2700, 4100 and 5000K

### Long Life

- 8,000-12,000 Hours Average Rated Life

### Benefits

- Saves energy
- Low maintenance
- Compact design

### Applications

- Table lamps
- Down lighting
- General lighting

Available in  
**Dimmable, 3-Way  
 and Colors.**

Call Halco today and get a great look at our vast product line, personal service and fast delivery. Visit us at [halcolighting.com](http://halcolighting.com).

Your account representative is your single source for pricing, orders, and technical support.

Shipping from Atlanta, Cleveland, Houston, and Phoenix.

**ISO 9001 Certified**



where there's light,  
 there's halco®



(800) 677-3334  
[halcolighting.com](http://halcolighting.com)

# ProLume® T3 Mini-Spirals



COMPACTS

Bulb Type	Watts	Base	Halco #	Product Code	Description	Inner/Master	Color Temp	CRI	Initial Lumens	Incandescent Equivalent	Avg Rated Life	MOL (Inches)
<b>T3 MINI-SPIRALS</b>												
T3	7	Med.	109247	CFL7/27	Warm White	10/50	2700	82	420	40	10000	4.13"
T3	7	Med.	109249	CFL7/41	Cool White	10/50	4100	82	420	40	10000	4.13"
T3	11	Med.	109240*	CFL11/27	Warm White	10/50	2700	82	700	40	8000	4.69"
T3	11	Med.	109242	CFL11/41	Cool White	10/50	4100	82	700	40	8000	4.69"
T3	11	Med.	109244	CFL11/50	Natural White	10/50	5000	82	700	40	8000	4.69"
T3	11	Med.	109224	CFL11/BLU	Blue	10/50	-	-	-	40	8000	4.69"
T3	11	Med.	109226	CFL11/GRN	Green	10/50	-	-	-	40	8000	4.69"
T3	11	Med.	109220	CFL11/RED	Red	10/50	-	-	-	40	8000	4.69"
T3	11	Med.	109222	CFL11/YEL	Yellow	10/50	-	-	-	40	8000	4.69"
T3	13	Med.	45101*	CFL13/27	Warm White	10/50	2700	82	900	60	10000	4.44"
T3	13	Med.	45103	CFL13/35	White	10/50	3500	82	900	60	10000	4.44"
T3	13	Med.	45104	CFL13/41	Cool White	10/50	4100	82	900	60	10000	4.44"
T3	13	Med.	45105	CFL13/50	Natural White	10/50	5000	82	900	60	10000	4.44"
T3	13	Med.	45107	CFL13/65	Daylight	10/50	6500	82	900	60	10000	4.44"
⊕ T3	14	Med.	46301*	CFL14/27/DIM	Warm White Dimmable	1/12	2700	82	925	60	8000	4.13"
T3	15	Med.	109252*	CFL15/27	Warm White	10/50	2700	82	950	60	12000	4.94"
T3	15	Med.	109330	CFL15/35	White	10/50	3500	82	950	60	12000	4.94"
T3	15	Med.	109261	CFL15/41	Cool White	10/50	4100	82	950	60	12000	4.94"
T3	15	Med.	109272	CFL15/50	Natural White	10/50	5000	82	950	60	12000	4.94"
T3	15	Med.	109270	CFL15/BLB	Black Light Blue	10/50	-	-	-	60	12000	4.94"
T3	15	Med.	109288	CFL15/YEL	Yellow	10/50	-	-	-	60	12000	4.94"
T3	18	Med.	45120*	CFL18/27	Warm White	10/60	2700	82	1200	75	12000	5.31"
T3	18	GU24	46512	CFL18/27/GU24	Warm White	10/60	2700	82	1200	75	10000	4.5"
T3	18	Med.	45122	CFL18/35	White	10/50	3500	82	1200	75	12000	5.31"
T3	18	Med.	45123	CFL18/41	Cool White	10/50	4100	82	1200	75	12000	5.31"
⊕ T3	18	GU24	46520	CFL18/41/GU24	Cool White	10/60	4100	82	1200	75	10000	4.5"
T3	18	Med.	45124	CFL18/50	Natural White	10/50	5000	82	1200	75	12000	5.31"
⊕ T3	18	GU24	46521	CFL18/50/GU24	Natural White	10/60	5000	82	1200	75	10000	4.5"
⊕ T3	18	Med.	45125	CFL18/65	Daylight	10/50	6500	82	1200	75	12000	5.31"
T3	20	Med.	109254*	CFL20/27	Warm White	10/50	2700	82	1200	75	12000	5.25"
T3	20	Med.	109332	CFL20/35	White	10/50	3500	82	1200	75	12000	5.25"
T3	20	Med.	109263	CFL20/41	Cool White	10/50	4100	82	1200	75	12000	5.25"
T3	20	Med.	109274	CFL20/50	Natural White	10/50	5000	82	1200	75	12000	5.25"
T3	23	Med.	45250*	CFL23/27	Warm White	10/50	2700	82	1600	100	10000	5.13"
⊕ T3	23	GU24	46518	CFL23/27/GU24	Warm White	10/60	2700	82	1600	100	10000	5"
T3	23	Med.	45252	CFL23/35	White	10/50	3500	82	1600	100	10000	5.13"
T3	23	Med.	45253	CFL23/41	Cool White	10/50	4100	82	1600	100	10000	5.13"
⊕ T3	23	GU24	46523	CFL23/41/GU24	Cool White	10/60	4100	82	1600	100	10000	5"
T3	23	Med.	45254	CFL23/50	Natural White	10/50	5000	82	1600	100	10000	5.13"
⊕ T3	23	GU24	46524	CFL23/50/GU24	Natural White	10/60	5000	82	1600	100	10000	5"
⊕ T3	24	Med.	46326	CFL24/27/DIM	Warm White Dimmable	1/12	2700	82	1600	100	8000	4.75"
⊕ T3	13/20/25	Med.	45720*	CFL25/27/3WAY	Warm White 3-Way	10/50	2700	82	900/1200/1550	30/70/100	8000	6.13"
⊕ T3	13/20/25	Med.	45721	CFL25/41/3WAY	Cool White 3-Way	10/50	4100	82	900/1200/1550	30/70/100	8000	6.13"
⊕ T3	26	GU24	46528	CFL26/27/GU24	Warm White	10/60	2700	82	1750	100	10000	5.2"
⊕ T3	26	GU24	46529	CFL26/41/GU24	Cool White	10/60	4100	82	1750	100	10000	5.2"
⊕ T3	26	GU24	46530	CFL26/50/GU24	Natural White	10/60	5000	82	1750	100	10000	5.2"
T3	27	Med.	109310*	CFL27/27	Warm White	10/50	2700	82	1750	100	10000	5.44"
T3	27	Med.	45255	CFL27/35	White	10/50	3500	82	1750	100	10000	5.44"
T3	27	Med.	109312	CFL27/41	Cool White	10/50	4100	82	1750	100	10000	5.44"
T3	27	Med.	109314	CFL27/50	Natural White	10/50	5000	82	1750	100	10000	5.44"
T3	32	Med.	109316*	CFL32/27	Warm White	10/50	2700	82	2100	125	10000	5.56"
T3	32	Med.	109318	CFL32/41	Cool White	10/50	4100	82	2100	125	10000	5.56"
T3	32	Med.	109306	CFL32/50	Natural White	10/50	5000	82	2100	125	10000	5.56"
T3	42	Med.	109328*	CFL42/27	Warm White	1/24	2700	82	2800	150	8000	7.06"
T3	42	Med.	109336	CFL42/41	Cool White	1/24	4100	82	2800	150	8000	7.06"
T3	42	Med.	109338	CFL42/50	Natural White	1/24	5000	82	2800	150	8000	7.06"

⊕ NEW ITEM!

(Hg) Hg-LAMP CONTAINS MERCURY, MANAGE IN ACCORD WITH DISPOSAL LAWS.

Visit [www.lamprecycle.org](http://www.lamprecycle.org) for disposal information for your state or local government.



**CAUTION:** Non-dimmable lamps should not be used on dimming circuits, timing devices, photo sensors or occupancy sensors. This device is not intended for use with emergency exit fixtures.

This device complies with Part 18 of the FCC Rules. This product may cause interference with radio equipment and should not be installed near maritime safety communications equipment, ships at sea or other critical navigation or communications equipment operating between 0.45-30 MHz.

**WARRANTY - Commercial / Industrial:** Dimmable lamps are warranted for 2 years from date of purchase based on 3 hours of use per day. Non-dimmable lamps are warranted for 2 years from date of purchase based on 10 hours of use per day.

Halco Lighting Technologies | P.O. Box 2834 | Norcross, GA 30091-2834

Toll Free 800.677.3334 | Phone 770.242.3612 | Fax 800.880.0822

[halcolighting.com](http://halcolighting.com)

Atlanta | Cleveland | Houston | Phoenix