


Bi-Pin JC SERIES

Only for Use in Approved Enclosed Halogen Fixtures
Average Life 2,000 Hours

| Watts | Item code | Description | Voltage (V) | Approx Lumens (lm) | Dimension | | | Avg. Life (Hours) | Base | Case Qty. |
|-------|--------------|-------------|-------------|--------------------|-----------|----------|----------|-------------------|-------|-----------|
| | | | | | Dia (in) | MOL (in) | LCL (in) | | | |
| 20 | H02012242801 | JC12V 20W | 12 | 350 | 0.31 | 1.30 | 0.87 | 2000 | G4 | 100 |
| *30 | H03012242801 | JC12V 30W | 12 | 510 | 0.31 | 1.30 | 0.87 | 2000 | G4 | 100 |
| 35 | H03512252801 | JC12V 35W | 12 | 595 | 0.39 | 1.73 | 1.06 | 2000 | G5.3 | 100 |
| 50 | H05012252801 | JC12V 50W | 12 | 900 | 0.39 | 1.73 | 1.06 | 2000 | G5.3 | 100 |
| *75 | H07512252801 | JC12V 75W | 12 | 1350 | 0.39 | 1.73 | 1.06 | 2000 | G5.3 | 100 |
| *100 | H10012252801 | JC12V 100W | 12 | 2000 | 0.45 | 1.73 | 1.18 | 2000 | G5.3 | 100 |
| 35 | H03512262801 | JC12V 35W | 12 | 595 | 0.39 | 1.73 | 1.18 | 2000 | G6.35 | 100 |
| 50 | H05012262801 | JC12V 50W | 12 | 900 | 0.39 | 1.73 | 1.18 | 2000 | G6.35 | 100 |
| 75 | H07512262801 | JC12V 75W | 12 | 1350 | 0.39 | 1.73 | 1.18 | 2000 | G6.35 | 100 |
| 100 | H10012262801 | JC12V 100W | 12 | 2000 | 0.45 | 1.73 | 1.18 | 2000 | G6.35 | 100 |

* Items only available for special orders

All measurements are shown in inches unless noted



G4 • G5.3 • G6.35 Base