

ISB SOLA BASIC



REV: "A"

FLUORESCENT BALLAST SPECIFICATIONS

DESCRIPTION

CATALOG E420-T-134-TP	TYPE Energy efficient magnetic	STARTING METHOD Rapid Start	NUMBER OF LAMPS 1	LAMP TYPE F40SST12, F40T12, F30T12, F30SST12
---------------------------------	-----------------------------------	--------------------------------	----------------------	---

ELECTRICAL CHARACTERISTICS

INPUT VOLTAGE 277v	LAMP WATTS 40/34/30/25w	INPUT WATTS 52w	INPUT CURRENT 0.20 A	OCV 220v	PF 0.96	FREQUENCY 60 Hz	SOUND RATED A
MIN START TEMP 50°F (60°Fw/SS lamp)	CLASS P	TYPE 1 outdoor	BALLAST FACTOR 0.95 (0.90w/SS lamp)	BEF 1.826	THD 12%	NO PCB'S	

PHYSICAL CHARACTERISTICS


	CASE DIMENSIONS						
	UNITS	M1	M2	M3	W	L	H
	INCHES	1.687	8.906	8.344	2.375	9.5	1.5
	TOL(+/-)	0.010	0.010	0.010	0.050	0.050	0.050
	MM	43	226	212	60	241	38
	TOL(+/-)	0.25	0.25	0.25	1.30	1.30	1.30
LEAD LENGTH							
UNITS	BLACK	WHITE	RED	BLUE			
INCHES	22	22	26	36			
TOL(+/-)	3/8	3/8	3/8	3/8			
MM	559	559	600	914			
TOL(+/-)	10	10	10	10			

CARTON CHARACTERISTICS

UNITS/CARTON 10	CARTONS/LAYER 12 & 4	# OF LAYERS 5 & 1	UNITS/PALLET 640	PIECE WEIGHT 3.5 lbs	CARTON WEIGHT 36 lbs	PALLET WEIGHT 2,337 lbs
CARTONS/PALLET 64	CARTON DIMENSIONS 12" x 12" x 4"	PALLET DIMENSIONS 40" x 48" x 7"	PALLET DIMENSIONS LOADED, INCLUDING WOOD PALLET 40" x 48" x 32"			

CARTON LABEL

ELECTRICAL DIAGRAM



PRODUCT LABEL

277 VOLT **0.20** AMP **430** OCV **60** HZ

FOR: 1-F40T12 or 1-F30T12 or at 15.5° C Min. amb.; 1-F40T12ES or 1-F30T12ES

MAXIMUM VOLTAGE BETWEEN RED AND BLUE: 220 V

SOUND RATED **A**

3 YEAR WARRANTY

HIGH POWER FACTOR RAPID START BALLAST

E420-T-134-TP

MINIMUM 10° C
MADE IN MEXICO

GROUND BALLAST CASE
MOUNT LAMP WITHIN 12" OF BRASS/STEEL METAL REFLECTOR

CLASS P
AUTOMATIC BURNING
THERMAL PROTECTION
TYPE 1 OUTDOOR
NON PCB

Lighting and Power Source
2707 Realty Road, Suite 110
Carrollton, TX 75006
Tel: (888) 385-4448
Fax: (972) 418-5858