


[Return to search](#)[Print Page](#)**Product Number:** 24082**Order Abbreviation:** FB40/D41/6**General Description:** 40W, T12 Curvalume rapid start fluorescent lamp, 6" leg spacing, Designer rare earth phosphor, 4100K color temperature, 70 CRI**Product Information**

Abbrev. With Packaging Info.	FB40D416 12/CS 1/SKU
Actual Length (in)	22.6
Actual Length (mm)	574.0
Average Rated Life (hr)	18000
Base	Medium Bipin
Bulb	T12
Color Rendering Index (CRI)	70
Color Temperature/CCT (K)	4100
Diameter (in)	1.59
Diameter (mm)	40.4
Family Brand Name	Designer
Industry Standards	ANSI C78.901 - 2001
Initial Lumens at 25C	3050
Mean Lumens at 25C	2745
Nominal Length (in)	22.5
Nominal Wattage (W)	40.00

Additional Product Information[Product Documents, Graphs, and Images](#)[Compatible Ballast](#)[Packaging Information](#)**Footnotes**

- Average rated life is measured at 3 hours per start on 2-lamp, rapid start magnetic ballasts per IES recommended practice. Lamp life on single-lamp rapid start ballasts may be reduced.
- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified conditions and with ballast meeting ANSI specifications. If burning cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.

[Print Page](#)