

## Series Features



- Solid State Charger
- Dual-Voltage Transformer for 120/277 VAC Operation
- Maximum Input Rating  
120VAC 60 Hz 4.0 Watt  
277VAC 60 Hz 4.0 Watt



- For Use on Single or Double Lamps
- Illuminates Rapid Start, Instant Start, High Output, Slim Line, Circline, U-Shaped or Compact Lamps



- Sealed Nickel Cadmium Battery
- Maintenance-Free



- Converts Fluorescent Fixtures to Emergency Lighting
- Provides 1.5-Hour Illumination for Single or Double Lamps
- Completely Self-Contained Inside or Above Lighting Fixture
- Compact Steel Housing
- Convenient Length Lead Wires
- Test Switch
- Red (Power On) Indicator
- Operating Range: 50°–140°F
- Warranty: 2–5 Years
- UL Listed



An affordable alternative to conventional emergency lighting, the EFB Series is a fluorescent ballast, which enhances existing AC fixtures by illuminating 1 or 2 lamps during a power failure.

## Dimensions

**EFB40-2**  
Height: 1.5"  
Length: 13.125"  
Width: 2.375"  
Mtg. Ctr.: 12.75"

**ALL OTHERS**  
Height: 1.5"  
Length: 9.5"  
Width: 2.375"  
Mtg. Ctr.: 9.0"

## Linear Lamps

Lamps Operated	Qty.	EFB40 500 Lumens	EFB80 700 Lumens	EFB40-2 1300 Lumens	EPLB13 650 Lumens	EPLB26 650 Lumens	EPLB42 650 Lumens
2'-4' Rapid, Instant Energy Saving, T8 and T12	1	X	X	X			
2'-4' Rapid, Instant Energy Saving, T8 and T12, HO & VHO	2		X**	X**			
5'-8' Rapid, Instant Energy Saving, T8 and T12, HO & VHO	1		X	X			
20W-40W Circline	1	X	X	X			
20W-40W Circline	2		X	X			

## Compact Lamps

Lamps Operated	Qty.	EFB40 500 Lumens	EFB80 700 Lumens	EFB40-2 1300 Lumens	EPLB13 650 Lumens	EPLB26 650 Lumens	EPLB42 650 Lumens
5-, 7-, 9- & 13-Watt Twin Tube (2 pin)	1				X		
9W-13W USA Quad Tube (2 pin)	1				X		
18W-26W Quad Tube (2 pin)*	1					X	
10W-26W Quad Tube (4 pin)	1 or 2						X
18W-39W Long Compact	1						X
40-Watt Biax	1		X	X			
50-Watt Biax	1			X			
55-Watt Biax	1			X			
18W-26W Triple Tube (4 pin)	1 or 2						X
32W-42W Triple Tube (4 pin)	1						X

\*22- & 28-Watt 15 mm lamps are not compatible.

\*\*Note: Two-lamp emergency is not possible with all electronic ballasts. Consult customer service for specific ballast compatibility.

## Ordering Information

<b>EFB40</b>	<b>-TMK</b>
Model	Options

## Options

Add Suffix to Catalog Number

- FC Flex Cord
- RTSK Remote Test Switch Kit (EFB Series)
- TMK Top Mount Kit

