



15W/ODR30



9W/ODGS



7W/ODA

**Integral Covered CFL**

Nominal Wattage	Overdrive Model #	Item Description & CCT	Lamp Base	Initial Lumen	Average Rated Life (Hrs.)	Dia Inches/mm	Length Inches/mm	Pack Inner/Master	Item #
● 15	15W/ODR30	15W R30 Reflector- CFL- Soft White	E26	650	6,000	3.7 / 95	5.4 / 137	25	037
15	15W/ODR30/50K	15W R30 Reflector- CFL- Natural DL	E26	650	10,000	3.7 / 95	5.4 / 137	25	091
9	15W/ODR30	15W R30 Reflector- CFL- Soft White	E26	500	10,000	3.1 / 80	4.8 / 123	25	036
7	15W/ODR30	15W R30 Reflector- CFL- Soft White	E26	450	10,000	2.1 / 54	4.3 / 108	50	077

**Features**

- 6,000 to 10,000 hour average rated life reduces relamping & related costs
- Rare earth tri-phosphor with 80 plus CRI for better performance
- High Luminous Efficacy
- 75% Lower Power Consumption over incandescent bulbs
- Available in various color temperature
- Compact in Size and fits most applications

**Applications**

- Industrial Lighting
- Wall Scones
- Recessed Cans
- Surface Ceiling Fixtures
- Down Lighting
- Showcase Lighting

A Type   G Type   R Type

- |   |   |   |
|---|---|---|
|   |   | ✓ |
| ✓ |   |   |
| ✓ | ✓ | ✓ |
| ✓ |   | ✓ |
| ✓ | ✓ | ✓ |
| ✓ | ✓ | ✓ |

**Notes**

- Not Dimmable
- Available in other color temperature also (upon request)
- Dimension with  $\pm$  0.1 inch tolerance

● Energy Star Qualified

