


- PRODUCT CATALOG
- ENLIGHTENING SHEETS
- ABOUT LITETRONICS
- LITETRONICS EDGE
- FIND A DISTRIBUTOR
- BECOME A DISTRIBUTOR
- NEWS & PRESS
- CAREERS
- TECH SUPPORT
- SUGGESTION BOX
- CONTACT LITETRONICS
- SUBSCRIBE TO LITELINE
- ENERGY SAVER CALCULATOR



Fluorescent Lighting

**SPIRAL-PAR™** LOW PROFILE Ultra Compact Fluorescent Lamps PAR38

PAR 38



RATED LIFE	APPLICATIONS	FEATURES AND BENEFITS
<ul style="list-style-type: none"> <li>- 8,000 hours</li> </ul>	<ul style="list-style-type: none"> <li>- General Lighting</li> <li>- Signs</li> <li>- Marquees</li> </ul>	<ul style="list-style-type: none"> <li>- Directly replaces incandescent lamps in most medium-based incandescent lighting fixtures.</li> </ul>







Watts	Base	Description	Ordering Code	Qty/Case	Avg. Rated Life	Lumens	M.O.L.**	CRI	CCT	MSDS
20	MED	20W SPLP PAR38 27	L-1271	10	8000	1100	5 7/8"	82	2700K	
20	MED	20W SPLP PAR38 41	L-1272	10	8000	1100	5 7/8"	82	4100K	

**MICRO BRITE™** Cold Cathode PAR38 Micro Compact Fluorescent Lamps

PAR 38



RATED LIFE	APPLICATIONS	FEATURES AND BENEFITS
<ul style="list-style-type: none"> <li>- 18,000 hours</li> </ul>	<ul style="list-style-type: none"> <li>- Signs</li> <li>- Marquees</li> <li>- Recessed Can Lighting</li> <li>- General Lighting</li> <li>- Outdoor Security Fixtures</li> </ul>	<ul style="list-style-type: none"> <li>- Directly replaces incandescent lamps in most medium-based incandescent lighting fixtures.</li> <li>- 2 year warranty</li> </ul>

Watts	Base	Volts	Description	Ordering Code	Qty/Case	Avg. Rated Life	Lumens	M.O.L.**	CRI	CCT	MSDS
8	MED	110-130	8W PAR38 F R	MB-850DR	6	18000	-	5 3/4"	-	RED	
8	MED	110-130	8W PAR38 F G	MB-850DG	6	18000	-	5 3/4"	-	GREEN	
8	MED	110-130	8W PAR38 F B	MB-850DB	6	18000	-	5 3/4"	-	BLUE	
8	MED	110-130	8W PAR38 F Y	MB-850DY	6	18000	-	5 3/4"	-	YELLOW	
8	MED	110-130	8W PAR38 F LO PW	MB-851DP	6	18000	305	5 3/4"	82	2850K	
8	MED	110-130	8W PAR38 F 4	MB-852D	6	18000	340	5 3/4"	82	4100K	

[Icon and terms glossary](#)

Subscribe to LITELINE

