

[Return to search](#)

[Print Page](#)



**Product Number:** 58313  
**Order Abbreviation:** 65MR16/T/FL35/C(FPB) 12V  
**General Description:** Tungsten Halogen Tru-Aim MR16 TITAN Axial Filament Hard Dichroic Reflector Cover Glass GU5.3 Bi-Pin Base 65Watt 12Volt Flood Beam

**Product Information**

Abbrev. With Packaging Info.	65MR16TFL35CFPB 12V 20/CS 1/SKU
ANSI Code	FPB
Average Rated Life (hr)	4000
Base	GU5.3 Bipin
Beam Angle (deg)	35
Beam Type	FL
Bulb	MR16
Centerbeam Candlepower (cp)	2000
Class	C (gas)
Color Temperature/CCT (K)	3000
Diameter (in)	2
Diameter (mm)	50.8
Ecologic	YES
Family Brand Name	TRU-AIM TITAN®
Filament	AXIAL
Horizontal Beam Angle (deg)	35
Maximum Overall Length - MOL (in)	1.750
Maximum Overall Length - MOL (mm)	44.45
Nominal Voltage (V)	12.00
Nominal Wattage (W)	65.00
Vertical Beam Angle (deg)	35

**Additional Product Information**

**Product Documents, Graphs, and Images**

**Packaging Information**



**Footnotes**

- Max. seal temperature 370 C (662F)
- UV Filter capsule with axial filament in covered constant color, hard coated dichroic reflector.
- Max pin temperature 250 C.
- Max temperature at lens reflector joint 240 C.