

[Return to search](#)[Print Page](#)

Product Number: 64471
Order Abbreviation: M175/U
General Description: 175W general lighting metal halide lamp, universal burn, clear

Product Information

Abbrev. With Packaging Info.	M175U 6/CS 1/SKU
ANSI Code	M57/E
Approx. Lumens (initial - horizontal)	12800
Approx. Lumens (initial - vertical)	14400
Approx. Lumens (mean - horizontal)	9300
Approx. Lumens (mean - vertical)	9300
Arc Length (in)	1.02
Arc Length (mm)	26
Average Rated Life - Horizontal (hr)	7500
Average Rated Life - (hr)	7500
Average Rated Life - Vertical (hr)	10000
Base	E39 Mogul
Bulb	BT28
Color Rendering Index (CRI)	65
Color Temperature/CCT (K)	4200
Diameter (in)	3.5
Diameter (mm)	89
Family Brand Name	Metalarc®
Fixture Requirement	E
Hot Restrike Time (min)	7-12
Lamp Finish	Clear
Light Center Length - LCL (in)	5
Light Center Length - LCL (mm)	127
Maximum Base Temperature - Fahrenheit	482
Maximum Base Temperature - Celsius	250
Maximum Bulb Temperature - Fahrenheit	752
Maximum Bulb Temperature - Celsius	400
Maximum Overall Length - MOL (in)	8.31
Maximum Overall Length - MOL (mm)	211
Nominal Voltage (V)	132.00

Nominal Wattage (W)	175.00
Operating Position	Universal
Warm-up Time (min)	2-4

Additional Product Information[Product Documents, Graphs, and Images](#)[Compatible Ballast](#)[Packaging Information](#)**Footnotes**

- E = Lamps classified as E-type are to be used ONLY in suitably enclosed luminaries. See lamp warning.

[Print Page](#)