

[Return to search](#)[Print Page](#)

**Product Number:** 64575  
**Order Abbreviation:** M400/U/ET18  
**General Description:** Compact 400W reduced outer jacket, universal burn metal halide lamp, clear

#### Product Information

|                                       |                       |
|---------------------------------------|-----------------------|
| Abbrev. With Packaging Info.          | M400UET18 10/CS 1/SKU |
| ANSI Code                             | M59/E                 |
| Approx. Lumens (initial - horizontal) | 33000                 |
| Approx. Lumens (initial - vertical)   | 36000                 |
| Approx. Lumens (mean - horizontal)    | 21500                 |
| Approx. Lumens (mean - vertical)      | 23400                 |
| Arc Length (in)                       | 1.77                  |
| Arc Length (mm)                       | 45                    |
| Average Rated Life - Horizontal (hr)  | 15000                 |
| Average Rated Life - (hr)             | 15000                 |
| Average Rated Life - Vertical (hr)    | 20000                 |
| Base                                  | E39 Mogul             |
| Bulb                                  | ET18                  |
| Color Rendering Index (CRI)           | 65                    |
| Color Temperature/CCT (K)             | 4000                  |
| Diameter (in)                         | 2.25                  |
| Diameter (mm)                         | 57                    |
| Family Brand Name                     | Compact Metalarc®     |
| Fixture Requirement                   | E                     |
| Hot Restrike Time (min)               | 7-12                  |
| Lamp Finish                           | Clear                 |
| Light Center Length - LCL (in)        | 9.75                  |
| Light Center Length - LCL (mm)        | 156                   |
| Maximum Base Temperature - Fahrenheit | 482                   |
| Maximum Base Temperature - Celsius    | 250                   |
| Maximum Bulb Temperature - Fahrenheit | 806                   |

|                                    |           |
|------------------------------------|-----------|
| Maximum Bulb Temperature - Celsius | 430       |
| Maximum Overall Length - MOL (in)  | 9 3/4     |
| Maximum Overall Length - MOL (mm)  | 248       |
| Nominal Voltage (V)                | 135.00    |
| Nominal Wattage (W)                | 400.00    |
| Operating Position                 | Universal |
| Warm-up Time (min)                 | 2-4       |

**Additional Product Information**[Product Documents, Graphs, and Images](#)[Compatible Ballast](#)[Packaging Information](#)**Footnotes**

- E = Lamps classified as E-type are to be used ONLY in suitably enclosed luminaries. See lamp warning.

[Print Page](#)