





Globe Lamps G25, G30, G40 Series Specifications


One Piece Compact Fluorescent Decorative Globe

- NPF, 8,000 Hours average rated life


Item #	Wattage	Incandescent Wattage Comparison	Initial Lumens	Input Line Current	M.O.L. (Inches)	Diameter (Inches)	Base
1G2504	4	25	250	.07A	4.2	3.1	Medium
1G2509	9	40	495	.15A	4.2	3.1	Medium
1G2509C	9	40	495	.15A	4.2	3.1	Candelabra
2G2514 ★	14	60	800	.23A	4.7	3.1	Medium
1G3009	9	40	495	.15A	5.0	3.7	Medium
1G3014 ★	14	60	800	.23A	5.0	3.6	Medium
1G3019 ★	19	75	950	.32A	4.9	3.7	Medium
1G4014	14	60	800	.23A	6.8	5.0	Medium
1G4019	19	75	950	.30A	6.8	5.0	Medium




SpringLamp Inside!



G25



G30




G40

Applications:

- Use anywhere a standard incandescent is used

Perfect for:



Special Application Options: (Ordering Suffix)

- 3100°K (31K), 3500°K (35K), 4100°K (41K), 5100°K (51K), 6500°K (65K),

Features and Benefits

- Long life, 8,000 hour average rated life
- Lasts 5 times longer than similar incandescent
- Replace less often, ideal for hard to reach places
- Lower maintenance and labor costs for lamp replacements
- 2700°K color temperature closest to incandescent light
- Quick run-up time
- Medium base and compact height fits anywhere a standard incandescent fits
- Instant start, flicker free
- End of Life logic guards against violent failures
- World class phosphor insures high lumen output and excellent lumen maintenance

Specifications

End of Life Protection-----	Yes
Ballast Type -----	Electronic
Starting Method -----	Modified Rapid Start
Input Line Voltage -----	120VAC
Input Line Frequency -----	60HZ
Lamp Life (rated) -----	8,000 Hours
Color Temperature -----	2700°K
Color Rendering Index -----	82
Min. Starting Temperature -----	20 ° F
Max. Operating Temperature --	160 ° F
U.L. / C.U.L. Listed -----	Yes
FCC Compliance -----	Part 18, Subpart C
Lamp Operating Frequency ---	45 KHZ
Lamp Current Crest Factor ----	< 1.60
Max. Open Circuit Voltage -----	600V
Power Factor -----	> .50
Total Harmonic Distortion -----	< 150%



ISO 9002
CERTIFIED

12 MONTH
WARRANTY