



23220 West 84th Street
Shawnee, KS 66227

800.852.2217
FAX 913.441.6679


www.eiko.com
eiko@eiko.com

MR16 STANDARD


MR16 Standard Front Glass (Continued)

	Ordering Code	Bar Code	Base	Volts	Watts	MOL in/mm	MOD in/mm	Filament	Approx. Init. Max Beam CP	Color Temp.	Avg. Life	Beam Angle °
	EXT-FG-24V	49566		GU5.3	24	50	1.99/50.5	2.00/50.8	C-8	10,000	3000	4000
EXZ-FG	15084		GU5.3	12	50	1.99/50.5	2.00/50.8	C-8	3000	3000	4000	24
EYC-FG	15092		GU5.3	12	75	1.99/50.5	2.00/50.8	C-8	2000	3050	4000	38
EYF-FG	15094		GU5.3	12	75	1.99/50.5	2.00/50.8	C-8	11,500	3050	4000	12
EYJ-FG	15096		GU5.3	12	75	1.99/50.5	2.00/50.8	C-8	5500	3080	4000	24
EYP-FG	15074		GU5.3	12	42	1.99/50.5	2.00/50.8	C-8	991	3000	4000	38
EYR-FG	15076		GU5.3	12	42	1.99/50.5	2.00/50.8	C-8	7070	3000	4000	12
EYS-FG	15078		GU5.3	12	42	1.99/50.5	2.00/50.8	C-8	2800	3000	4000	24
FMT-FG	15053		GU5.3	12	35	1.99/50.5	2.00/50.8	C-8	4800	2950	4000	12
FMV-FG	15055		GU5.3	12	35	1.99/50.5	2.00/50.8	C-8	1800	2950	4000	24
FMW-FG	15057		GU5.3	12	35	1.99/50.5	2.00/50.8	C-8	900	2950	4000	38
FNC-FG (Yellow)	15048		GU5.3	12	50	1.99/50.5	2.00/50.8	C-8	N/A	N/A	4000	12
FND-FG (Red)	15050		GU5.3	12	50	1.99/50.5	2.00/50.8	C-8	N/A	N/A	4000	12
FNE-FG (Green)	15052		GU5.3	12	50	1.99/50.5	2.00/50.8	C-8	N/A	N/A	4000	12
FNF-FG (Blue)	15054		GU5.3	12	50	1.99/50.5	2.00/50.8	C-8	N/A	N/A	4000	12
FNV-FG	00297		GU5.3	12	50	1.75/44.5	2.00/50.8	C-8	550	3000	3000	60
FPA-FG	15086		GU5.3	12	65	1.99/50.5	2.00/50.8	C-8	11,500	3050	4000	12
FPB-FG	15088		GU5.3	12	65	1.99/50.5	2.00/50.8	C-8	2000	3050	4000	38
FPC-FG	15090		GU5.3	12	65	1.85/47.0	2.00/50.8	C-8	4100	3050	4000	24
FRA-FG	49433		GU5.3	12	35	1.99/50.5	2.00/50.8	C-8	2800	3050	4000	18


MR16 Intermediate Screw Base

	Ordering Code	Bar Code	Base	Volts	Watts	MOL in/mm	MOD in/mm	Filament	Approx. Init. Max Beam CP	Color Temp.	Avg. Life	Beam Angle °
	FSA	15100		E17	120	75	2.75/69.6	2.00/50.8	CC-8	5000	3000	2000
FSB	15102		E17	120	75	2.75/69.6	2.00/50.8	CC-8	1800	3000	2000	20
FSC	15104		E17	120	100	2.75/69.6	2.00/50.8	CC-8	7000	3000	2000	12
FSD	15106		E17	120	75	2.75/69.6	2.00/50.8	CC-8	1300	3000	2000	30
FSE	15108		E17	120	100	2.75/69.6	2.00/50.8	CC-8	2400	3000	2000	20
FSF	15110		E17	120	100	2.75/69.6	2.00/50.8	CC-8	1750	3000	2000	30

MR16 Medium Screw Base

	Ordering Code	Bar Code	Base	Volts	Watts	MOL in/mm	MOD in/mm	Filament	Approx. Init. Max Beam CP	Color Temp.	Avg. Life	Beam Angle °
	10451	10451		E26	120	75	2.84/72.0	2.00/50.8	CC-8	5000	3000	2000
10452	10452		E26	120	75	2.84/72.0	2.00/50.8	CC-8	1800	3000	2000	20
10453	10453		E26	120	75	2.84/72.0	2.00/50.8	CC-8	1300	3000	2000	30

MR16 Silver & Black Coated Reflector

	Ordering Code	Bar Code	Base	Volts	Watts	MOL in/mm	MOD in/mm	Fil.	Approx. Init. Max Beam CP	Color Temp.	Avg. Life	Beam Angle °	Special Desc.
	BAB-BLACK	81109		GU5.3	12	20	1.81/46.0	2.00/50.8	C-8	460	2950	3000	38
BAB-SILVER	81108		GU5.3	12	20	1.81/46.0	2.00/50.8	C-8	460	2950	3000	38	Silver Reflector
EXN-BLACK	81115		GU5.3	12	50	1.77/44.5	2.00/50.8	C-8	1800	3000	4000	38	Black Reflector
EXN-SILVER	81114		GU5.3	12	50	1.77/44.5	2.00/50.8	C-8	1800	3000	4000	38	Silver Reflector
EXZ-BLACK	81113		GU5.3	12	50	1.77/45.0	2.00/50.8	C-8	3000	3000	4000	24	Black Reflector
EXZ-SILVER	81112		GU5.3	12	50	1.77/45.0	2.00/50.8	C-8	3000	3000	4000	24	Silver Reflector
FMW-BLACK	81111		GU5.3	12	35	1.81/46.0	2.00/50.8	C-8	900	2950	4000	38	Black Reflector
FMW-SILVER	81110		GU5.3	12	35	1.81/46.0	2.00/50.8	C-8	900	2950	4000	38	Silver Reflector