



[CustomerService](#) | [Ballasts](#) / [Transformers](#) | [Lamps](#) | [Custom Products](#) | [Company](#)



## FLUORESCENT IN-FIXTURE ELECTRONIC BALLAST

10 BALLASTS OPERATE 132 LAMPS IN 860 COMBINATIONS

- Solid State Electronics • High Power Factor • Small Case Size
- Lightweight • Versatile • Energy Saving

**WH1-120-L**

### Ballast Specifications

Maximum Power: 28W  
 Model Number: WH1-120-L  
 Maximum Current: .20 AMP  
 Operating Voltage: 120 VAC  
 Product Photo: [click here to view](#)

### Case Specifications

Black/White Wires: 12"  
 Red/Yellow Wires: 24"  
 Ballast Case Size: H .75" x W 1" x L 7.5"  
 Ballast Weight: 4.5 oz.  
 Case Quantity: 50 pcs.  
 Case Weight: 15 lbs.

### Specifications Common to all WorkHorse Ballasts

Frequency: 50/60 Hz	Regulatory Approvals: UL & cUL Listed Type 1 Outdoors
ATHD: Meets ANSI C82.11-1993	High Power Factor: >.90
Protection/Overcurrent: Fuse	Open Circuit Voltage: 600 V RMS Max.
Protection/Voltage Transients: MOV (PER ANSI C82.11 - 1993)	Min. Operating Temp.: -20* F (-30* C)
EMI/RFI: FCC PART 18-A	Max. Case Temp.: 158* F (70* C)
	Lamp Starting Mode: Instant Start
	Class P: Thermal
	Sound Rating: A