



Commercial Products &amp; Solutions

 [SITE SEARCH](#)
[HOME](#)[PRODUCTS](#)[EDUCATION / RESOURCES](#)[LIGHTING APPLICATIONS](#)
[Where to Buy](#) | [FAQs](#) | [Contact Us](#) | [EliteNet](#)
[Products](#) > [Halogen](#) > [MR](#) > [MR16](#) > 20833
**20833 – Q50MR16/C/FL40**


GE ConstantColor® Precise™ MR16

**GENERAL CHARACTERISTICS**

Lamp type	Halogen - MR
Bulb	MR16
Base	2-Pin (GX5.3)
Filament	C-6
Wattage	50
Voltage	12
Rated Life	6000 hrs
Lamp Enclosure Type (LET)	Open or enclosed fixtures



Bulb



Base



Filament

[View Larger](#)**PHOTOMETRIC CHARACTERISTICS**

Center Beam Candlepower (CBCP)	1700
Color Temperature	3050 K
Nominal Initial Lumens per Watt	34

**DIMENSIONS**

Maximum Overall Length (MOL)	1.8750 in (47.6 mm)
Bulb Diameter (DIA)	2.000 in (50.8 mm)

**PRODUCT INFORMATION**

Product Code	20833
Description	Q50MR16/C/FL40
ANSI Code	EXN
Standard Package	BUNDLE
Standard Package GTIN	00043168208338
Standard Package Quantity	20
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	20
UPC	043168994262

**⚠ CAUTIONS & WARNINGS**
[See list of cautions & warnings.](#)
**ADDITIONAL RESOURCES****Catalogs****Testimonials****Brochures**

Application/Segment Brochures

- [Beauty Salon Lighting](#)
- [Contractor Lighting](#)
- [Healthcare Lighting](#)
- [Office Lighting](#)
- [Specialty Store Lighting](#)

Product Brochures

- [Color](#)
- [XL Brochure](#)

**Sell Sheets**

- [GE ConstantColor® Precise™ MR16 Lamps](#)

**IES/Photometric Download****MSDS (Material Safety Data Sheets)****Disposal Policies & Recycling Information**[Return To Top](#)

---

[Home](#) | [Products](#) | [EliteNet](#) | [Education/Resources](#) | [Lighting Applications](#) | [Where to Buy](#) | [FAQs](#) | [Contact Us](#) | [Site Map](#)  
[Products for Your Home](#) | [Press Room](#) | [Corporate](#) | [Investor Information](#) | [Privacy Policy](#) | [Accessibility Statement](#) | [Terms of Use](#)

Copyright General Electric Company 1997-2008