




Commercial Products & Solutions

 [SITE SEARCH](#)
[HOME](#)[PRODUCTS](#)[EDUCATION / RESOURCES](#)[LIGHTING APPLICATIONS](#)
[Where to Buy](#) | [FAQs](#) | [Contact Us](#) | [EliteNet](#)
[Products](#) > 71714**71714 – GE332MAX-H/ULTRA**

GE LFL UltraMax™ Electronic High Efficiency Multivolt Instant Start Ballast



- Energy saving high efficiency instant start electronic ballast (> 90%)
- Multi-Voltage Technology handles voltage from 120 to 277V
- UL Type CC Rating provides protection against arcing in electrical devices.
- Active Current Regulation regulates the output to each lamp with individual lamp inverter modules.
- Anti-Striation Control for better light quality, with no striations.

[View Larger](#)**GENERAL CHARACTERISTICS**

Application	3 or 2- F32T8 120 to 277
Category	Linear Fluorescent
Ballast Type	Electronic - High Efficiency Multivolt Instant Start
Starting Method	Instant start
Lamp Wiring	Parallel
Line Voltage Regulation (+/-)	10 %
Ambient Temperature (MAX)	105 °C (221 °F)
Case Temperature (MAX)	70 °C (158 °F)
Ballast Factor	High (1.15)
Power Factor Correction	Active
Sound Rating	A (20-24 decibels)
Additional Info	Anti-striation control, Auto-restart, Thermally protected

ELECTRICAL CHARACTERISTICS


Supply Current Frequency	50 Hz/60 Hz
--------------------------	-------------

PRODUCT INFORMATION

Product Code	71714
Description	GE332MAX-H/ULTRA
Standard Package	Case
Standard Package GTIN	10043168717141
Standard Package Quantity	10
Sales Unit	Standard Pack
No Of Items Per Sales	1

DIMENSIONS

Case dimensions			
Length (L)	9.5 in (241.30 mm)		
Width (W)	1.7 in (43.18 mm)		
Height (H)	1.2 in (30.48 mm)		
Mounting dimensions			
Mount Length (M)	9.0 in (228.60 mm)		
Mount Width (X or F)	1.1 in (26.67 mm)		
Mount Slots (MS)	0.3 in (8.20 mm)		
Weight	1.40 lbs		
Exit Type	Side		
Remote mounting distance to lamp	18 ft		
Remote Mounting Wire Gauge	18 AWG		
Lead lengths	Qty	Exit	Length (± 1 in.)
Black	1	Left	25.0 in (635 mm)
White	1	Left	25.0 in (635 mm)
Red	1	Right	41.0 in (1041 mm)
Blue	1	Right	34.0 in (864 mm)



Unit

No Of Items Per
Standard Package

10

[View Larger](#)

UPC

043168717144

SPECIFICATIONS BY LAMP & WATTAGE

Lamp	# of Lamps	Line Volts	System Watts	Nom. Line Current	System Ballast Factor	Ballast Efficacy Factor	Power Factor % (>=)	Crest Factor (<=)	THD% (<=)	Min. Starting Temp (F/C)	
FE15T8	2	120	37	0.33 A	1.13	3.05	99	1.4	10	-22.0 / -30	System specs
	2	277	37	0.16 A	1.13	3.05	95	1.4	21	-22.0 / -30	System specs
	3	120	48	0.42 A	1.03	2.15	99	1.4	10	-22.0 / -30	System specs
	3	277	48	0.20 A	1.03	2.15	97	1.4	19	-22.0 / -30	System specs
F40T8	2	120	94	0.89 A	1.26	1.34	99	1.4	10	-22.0 / -30	System specs
	2	277	92	0.37 A	1.26	1.37	97	1.4	15	-22.0 / -30	System specs
F32T8/WM	2	120	79	0.70 A	1.26	1.59	99	1.4	10	50.0 / 10	System specs
	2	277	78	0.30 A	1.26	1.62	97	1.4	16	50.0 / 10	System specs
	3	120	104	0.91 A	1.18	1.13	99	1.4	10	50.0 / 10	System specs
	3	277	102	0.38 A	1.18	1.16	98	1.4	10	50.0 / 10	System specs
F32T8/25W	2	120	70	0.61 A	1.26	1.80	99	1.4	10	50.0 / 10	
	2	277	69	0.27 A	1.26	1.83	97	1.4	10	50.0 / 10	
	3	120		0.79 A	1.18		99	1.4	10	50.0 / 10	
	3	277		0.34 A	1.18		98	1.4	10	50.0 / 10	
F32T8	2	120	85	0.75 A	1.29	1.52	99	1.4	10	-22.0 / -30	System specs
	2	277	84	0.32 A	1.29	1.54	97	1.4	16	-22.0 / -30	System specs
	3	120	111	0.99 A	1.18	1.06	99	1.4	10	-22.0 / -30	System specs
	3	277	109	0.41 A	1.18	1.08	98	1.4	10	-22.0 / -30	System specs
F28T8	2	120	73	0.65 A	1.26	1.73	99	1.4	10	50.0 / 10	System specs
	2	277	72	0.28 A	1.26	1.75	97	1.4	17	50.0 / 10	System specs
	3	120	95	0.83 A	1.18	1.24	99	1.4	10	50.0 / 10	System specs
	3	277	94	0.35 A	1.18	1.26	98	1.4	10	50.0 / 10	System specs
F25T8	2	120	70	0.62 A	1.26	1.80	99	1.4	10	-22.0 / -30	System specs
	2	277	68	0.26 A	1.26	1.85	97	1.4	18	-22.0 / -30	System specs
	3	120	90	0.79 A	1.14	1.27	99	1.4	10	-22.0 / -30	System specs
	3	277	90	0.34 A	1.14	1.27	98	1.4	10	-22.0 / -30	System specs

F25T12	2	120	71	0.63 A	1.23	1.73	99	1.4	10	-22.0 / -30	System specs
	2	277	71	0.27 A	1.23	1.73	97	1.4	17	-22.0 / -30	System specs
	3	120	94	0.83 A	1.10	1.17	99	1.4	10	-22.0 / -30	System specs
	3	277	92	0.35 A	1.10	1.20	98	1.4	13	-22.0 / -30	System specs
F17T8	2	120	47	0.41 A	1.27	2.70	99	1.4	10	-22.0 / -30	System specs
	2	277	47	0.20 A	1.27	2.70	95	1.4	21	-22.0 / -30	System specs
	3	120	61	0.53 A	1.15	1.89	99	1.4	10	-22.0 / -30	System specs
	3	277	60	0.23 A	1.15	1.92	97	1.4	10	-22.0 / -30	System specs

Safety & Performance

RoHs Compliant



UL Type 1 Outdoor



UL Type HL

FCC - CLASS A Non-Consumer



UL Class P

cUL Listed



NEMA Premium®



UL Type CC



UL Listed

[See list of cautions & warnings.](#)

WARRANTY INFORMATION

GE Lighting warrants to the purchaser that each ballast will be free from defects in material or workmanship for period as defined in the attached documents from the date of manufacture when properly installed and under normal conditions of use.

[Download full warranty](#)

ADDITIONAL RESOURCES

Catalogs

Testimonials

Brochures

Application/Segment Brochures

- [UltraMax™ Brochure](#)
- [Retail Lighting](#)
- [Office Lighting](#)
- [Healthcare Lighting](#)
- [Contractor Lighting](#)
- [Property Management](#)

Product Brochures

- [Industrial Lighting](#)

Sell Sheets

- [General Specifications - T8 High Efficiency Instant Start](#)

[Disposal Policies & Recycling Information](#)

Photos are representational only. Sizes, shapes and labels of ballast may vary.

[Return To Top](#)