

## Product Description

The RC6 is a recessed housing for new construction designed to accommodate all Cree 6-inch downlights. Its maximum wattage is rated at 12 watts, ensuring the benefits of the low energy consumption are realized in the calculation of energy density for energy code compliance and LEED certification. The RC6 is IC rated, airtight, inherently protected and California Title-24 compliant when ordered with the GU24 socket.

## Compatibility Information

### RC6-12W

- CR6
- LR6
- LE6

### RC6-12W-GU24

- CR6-GU24
- LR6-GU24
- LE6-GU24
- LR6-DR1000
- LR6-DR650

## Ordering Information

- RC6-12W – Recessed housing with Edison socket.
- RC6-12W-GU24 – Recessed housing with GU24 socket. (Title-24 Applications)

## Product Information

- Recessed housing with integral nailer and ceiling grid attachment detail.
- Integral bar hanger spans from 14" to 24 1/2"
- Dimensions h = 7 1/2", w = 7 1/2", l = 12 1/2"
- Accommodates ceiling thickness from 1/4" to 1 1/4"
- Suitable for insulated or non-insulated ceilings.
- Air tight rated – tested in accordance with ASTM E283.
- Title-24 compliant when utilized with GU24 socket.
- Gasket on bottom of housing for seal between housing and ceiling material for Title-24 compliance.
- cETLus Listed™. Suitable for damp locations.

