

EnduraLED 3W 2700K BATT Dimmable

Product family description

The Philips EnduraLED[™] Candles offer decorative energy saving ambience with the elegant effect of incandescent candles. Available in bent and blunt tip shapes, their unique design provides light in all directions, giving lighting designers a long life alternative to incandescent sources. Energy saving, long life decorative LED candles lower cost with reduced wattage and re-lamp frequency.

Features

- Instant-on light.
- Emits virtually no UV/IR light in the beam.
- Similar ambience as traditional incandescent candles.
- 3000K color temperature.
- Designed to last 15,000 hours rated average life (1,2)
- 3-year Warranty period.
- Contains no mercury
- Rated average life is the length of operation (in hours) at which point an average of 50% of the lamps will still be operational and 50% will not.
- Available in 3 Watt Clear and Frost, Blunt and Bent tip.

Benefits

- Philips is the global leader in light and a leader in LED technology.
- Philips knows LED light and stands behind the EnduraLED products with a warranty.
- Philips' commitment to innovation and quality provides the confidence of partnering with an industry leader.

Application

· Ideal for wall sconces and decorative lighting.

Product data		
ProNumUS	410209	
Full product name	EnduraLED 3W 2700K BATT Dimmable	
OrdCodUS	410209	



Product data	
Pack type	
Pieces per Sku	I construction of the second se
Skus/Case	8
EANTUS	
EAN2US	
EAN3US	
Successor Product number	
Additional Information	Dimmable
Cap-Base	E12
Bulb	BALL
Wattage	3W
Dimmable	Yes
Color Code	WW
Color Designation (text)	Warm White
Correlated Color Temperature	2700 K
Luminous Flux	70 Lm
Color rendering index	90
Color Temperature	2700K [CCT 2700K]



LED EI2 BAII CL



©2009 Koninklijke Philips Electronics N.V.

All rights reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liablity will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent- or other industrial or intellectual property rights. Document order number : 0000 000 00000