

Philips EnduraLED Candle LED Lamp

Ideal for wall sconces and decorative fixtures

**EnduraLED** 

# Energy saving elegance

Philips EnduraLED Candle LED Lamps offer decorative, energy-saving ambience with the elegant effect of incandescent candles. The unique design provides light in all directions, giving lighting designers an alternative to incandescent sources.

## High efficacy LED decorative light

- · Instant-on light
- Emits virtually no UV/IR light in the beam
- 2W Candle LED lamps have a 20,000 hours rated average life<sup>1</sup>
- · Supplies light in both clear and frosted designs
- Similar ambience as traditional incandescent candles
- Contains no mercury

### Easy to experience

- Lowers maintenance costs by reducing re-lamp frequency
- · Installs into existing candelabra base fixtures
- 3-year limited warranty

(I See back page for footnotes)



# Philips EnduraLED Candle LED Lamp

# Ordering, Electrical and Technical Data (Subject to change without notice)

Product Number	Ordering Code	Nom. Watts	Volts	Lamps per SKU	Description	Bulb Type	Base	Rated Avg. Life (Hrs.)	Approx. Lumens <sup>2</sup>	CRI	Color Temp. (Kelvin)	MOL (In.)
40797-2	2B10 ½ END/CL/2700K 120V 8/I	2	120	I	EnduraLED B10½ 2W Candelabra Base Clear Lamp	B10½	Candelabra	20,000	70	90	2700	3.7
40796-4	2BA9 END/CL/ 2700K I20V 8/I	2	120	I	EnduraLED BA9 2W Candelabra Base Clear Lamp	BA9	Candelabra	20,000	70	90	2700	4.0
40605-8	3BA9 END/CL WW 120V 8/I	2.5	120	I	EnduraLED BA9 2.5W Candelabra Base Clear Lamp	BA9	Candelabra	15,000	32	80	3000	4.1
40606-6	3BA9 END/FR WW 120V 8/1	2.5	120	I	EnduraLED BA9 2.5W Candelabra Base Frosted Lamp	BA9	Candelabra	15,000	30	80	3000	4.1
40607-4	3B10½END/CL WW 120V 8/I	2.5	120	I	EnduraLED B10½ 2.5W Candelabra Base Clear Lamp	B10½	Candelabra	15,000	32	80	3000	4.0
40608-2	3B10½END/FR WW 120V 8/I	2.5	120	I	EnduraLED B10½ 2.5W Candelabra Base Frosted Lamp	B10½	Candelabra	15,000	30	80	3000	4.0

# **Shipping Data** (Subject to change without notice)

Product Number	SKU UPC (0-46677)	Outer Bar Code (5-00-46677)	Case Qty.	Case Weight (lbs.)	Case Cube (cu. ft.)	Pallet Qty.	SKUs Per Layer	Layers High	SKU Dimensions (W x D x H)(In.)		Pallet Dimensions (W x D x H)(ln.)
40797-2	40797-I	40797-6	8	8.0	0.06	3840	640	6	$1.4 \times 1.4 \times 4.2$	3.4 x 6.5 x 4.7	39.0 x 46.3 x 28.1
40796-4	40796-4	40796-9	8	8.0	0.06	3840	640	6	$1.4 \times 1.4 \times 4.2$	$3.4 \times 6.5 \times 4.7$	39.0 x 46.3 x 28.1
40605-8	40605-9	40605-4	8	8.0	0.06	3840	640	6	$1.4 \times 1.4 \times 4.2$	$3.4 \times 6.5 \times 4.7$	39.0 x 46.3 x 28.1
40606-6	40606-6	40606-I	8	8.0	0.06	3840	640	6	$1.4 \times 1.4 \times 4.2$	$3.4 \times 6.5 \times 4.7$	39.0 x 46.3 x 28.1
40607-4	40607-3	40607-8	8	8.0	0.06	3840	640	6	$1.4 \times 1.4 \times 4.2$	$3.4 \times 6.5 \times 4.7$	39.0 x 46.3 x 28.1
40608-2	40608-0	40608-5	8	0.8	0.06	3840	640	6	$1.4 \times 1.4 \times 4.2$	$3.4 \times 6.5 \times 4.7$	39.0 x 46.3 x 28.1

<sup>1)</sup> Rated average life based on engineering testing and probability analysis.

#### WARNINGS AND CAUTIONS

- Suitable for use in open luminaires (fixtures).
- Do not use in outdoor fixtures.
- Do not use in enclosed fixtures.
- Not for use with dimmers.
- Do not use with emergency exit fixtures or emergency lights.
- Turn off power before changing lamp.

**CAUTION:** Risk of electric shock. Use in dry location only.

**NOTES:** This device complies with Part 18 of the FCC rule. This product may cause interference with other devices. If interference occurs, change the location of the products involved. This RFLD device complies with Canadian ICES-005.





© 2011 Philips Lighting Company. A Division of Philips Electronic North America Corporation. All rights reserved. Printed in USA 2/11

A Division of Philips Electronics North America Corporation

<sup>2)</sup> Photometric testing consistent with IES LM-79.