

Philips EnduraLED R20 Dimmable Indoor Flood LED Lamp

Ideal for general lighting in retail, hospitality, and residential spaces

EnduraLED

Highlight with dimmable LED retrofit downlighting

Philips EnduraLED R20 Dimmable Indoor Flood LED Lamps bring innovation to familiar applications and deliver excellent dimming performance.

High efficacy LED narrow flood light

- Dims to 10% of full light levels* with excellent beam control
- Instant-on light
- Emits virtually no UV/IR light in the beam
- 45,000 hour rated average life!
- Projects a 22° beam angle
- Saves 34 watts of energy when compared to a 40W halogen R20**
- · Contains no mercury

Easy to experience

- Lowers maintenance costs by reducing re-lamp frequency
- Will not fade colors, avoids inventory spoilage
- 3-year limited warranty

(I, *, ** See back page for footnotes)



Philips EnduraLED R20 Dimmable Indoor Flood LED Lamp

Ordering, Electrical and Technical Data (Subject to change without notice)

				Lamps				Rated				Color	
	Ordering	Nom.		per		Bulb			Approx.				MOL
Number	Code	Watts	Volts	SKU	Description	Туре	Base	(Hrs.) ^I	Lumens ²	MBCP ^{2,3}	CRI	(Kelvin)	(ln.)
40826-0	6R20/END/F22 2700	6	120	I	120V EnduraLED	R20	Med.	45,000	200	900	81	2700	3.9
	DIM 6/I				Dimmable R20 22°								
40820-3	6R20/END/F22 3000	6	120	- 1	120V EnduraLED	R20	Med.	45,000	210	900	83	3000	3.9
	DIM 6/I				Dimmable R20 22°								

Shipping Data (Subject to change without notice)

		Outer		Case	Case		SKUs				
Product	SKU UPC	Bar Code	Case	Weight	Cube	Pallet	Per				Pallet Dimensions
Number	(0-46677)	(5-00-46677)	Qty.	(lbs.)	(cu. ft.)	Qty.	Layer	High	$(W \times D \times H)(In.)$	$(W \times D \times H)(In.)$	$(W \times D \times H)(In.)$
40826-0	40826-8	40796-9	6	3.2	0.196	1050	150	7	2.6 x 2.6 x 4.1	$7.2 \times 9.8 \times 4.8$	43.1 x 49.1 x 33.7
40820-3	40820-6	40797-6	6	3.2	0.196	1050	150	7	$2.6 \times 2.6 \times 4.1$	$7.2 \times 9.8 \times 4.8$	43.1 x 49.1 x 33.7

I) Rated average life based on engineering testing and probability analysis.

Energy Efficiency

Estimated Lighting Costs Using a 40W Halogen R20								
Present Wattage		40	W					
x Annual Operating Hours		3,000	hrs					
	=	120,000	watts per year					
÷1,000	=	120	kWh per year					
x kWh rate of \$0.10	=	\$12	per year					
x 100 lamps per space	=	\$1200	annual energy cost per space					

Estimated Lighting Costs Using	- Dhiline	7\A/ Ende	vol ED B20 Lover
Estimated Lighting Costs Using	a Philips	/ VV Endu	raLED K20 Lamp
Present Wattage		7	W
x Annual Operating Hours		3,000	hrs
	=	21,000	watts per year
÷1,000	=	21	kWh per year
x kWh rate of \$0.10	=	\$2	per year
x 100 lamps per space	=	\$210	annual energy cost per space

\$990

This energy saving example shows an application of 100 lamps in a space currently using a 40W halogen R20, operating 3,000 hours per year at a cost of \$0.10 per kWh.† Your actual savings may vary depending on the energy costs in your geographic location.

Replacing 100 40W halogen R20 lamps with the Philips 7W EnduraLED R20 lamps can provide significant energy cost savings of \$990 per year! Potential savings from the reduction in HVAC costs as a result of using a lower wattage lamp that emits less heat is an additional benefit not included in this example.

WARNINGS AND CAUTIONS

• Suitable for use in open luminaires (fixtures).

Total Estimated Annual Savings

- Do not use in outdoor fixtures.
- Do not use in enclosed fixtures.
- Turn off power before changing lamp.

CAUTION: Risk of electric shock. Use in dry location only.

NOTES: This device complies with Part 18 of the FCC rule. This product may cause interference with other devices. If interference occurs, change the location of the products involved. This RFLD device complies with Canadian ICES-005.





© 2011 Philips Lighting Company, A Division of Philips Electronics North America Corporation. All rights reserved. Printed in USA 2/11 P-6089-B

www.philips.com

Philips Lighting Company 200 Franklin Square Drive Somerset, NJ 08873 1-800-555-0050

Philips Lighting 281 Hillmount Road Markham, Ontario Canada L6C 2S3 1-800-555-0050 A Division of Philips Electronics Ltd.

²⁾ Photometric testing consistent with IES LM-79

³⁾ Maximum Beam Candlepower.

^{*} Designed for "Leading Edge" TRIAC dimming systems ** Light output of the 7W EnduraLED R20 at 500 candela compares to the 40W halogen R20 at 450 candela.

[♦] Based on 100 lamps per space operating at 3,000 hours per year.

[†] Light output of the 7W EnduraLED R20 at 500 candela compares to the 40W halogen R20 at 450 candela.