

[Return to search](#)

[Print Page](#)



Product Number: 58305
Order Abbreviation: 35MR16/T/FL35/C(FMW) 12V
General Description: Tungsten Halogen Tru-Aim MR16 TITAN Axial Filament Hard Dichroic Reflector Cover Glass GU5.3 Bi-Pin Base 35Watt 12Volt Flood Beam


Product Information

| | |
|-----------------------------------|---------------------------------|
| Abbrev. With Packaging Info. | 35MR16TFL35CFMW 12V 20/CS 1/SKU |
| ANSI Code | FMW |
| Average Rated Life (hr) | 4000 |
| Base | GU5.3 Bipin |
| Beam Angle (deg) | 35 |
| Beam Type | FL |
| Bulb | MR16 |
| Centerbeam Candlepower (cp) | 1500 |
| Class | C (gas) |
| Color Rendering Index (CRI) | 100 |
| Color Temperature/CCT (K) | 3000 |
| Diameter (in) | 2 |
| Diameter (mm) | 50.8 |
| Ecologic | YES |
| Family Brand Name | TRU-AIM TITAN® |
| Filament | AXIAL |
| Horizontal Beam Angle (deg) | 35 |
| Maximum Overall Length - MOL (in) | 1.750 |
| Maximum Overall Length - MOL (mm) | 45.0 |
| Nominal Voltage (V) | 12.00 |
| Nominal Wattage (W) | 35.00 |
| Vertical Beam Angle (deg) | 35 |

Additional Product Information

[Product Documents, Graphs, and Images](#)

[Packaging Information](#)



**Footnotes**

- Max. seal temperature 370 C (662F)
- UV Filter capsule with axial filament in covered constant color, hard coated dichroic reflector.
- Max pin temperature 220 C.
- Max temperature at lens reflector joint 240 C.
- Suitable for use in unshielded fixtures. Consult most recent luminaire standards for your area to determine luminaire requirements.

[Print Page](#)