

[Return to search](#)

[Print Page](#)



**Product Number:** 58317  
**Order Abbreviation:** 35MR16/B/FL35 12V  
**General Description:** Tungsten Halogen Tru-Aim MR16 Brilliant Axial Filament Aluminized Reflector GU5.3 Bi-Pin Base 35Watt 12Volt Flood Beam

**Product Information**

Abbrev. With Packaging Info.	35MR16BFL35 12V 20/CS 1/SKU
Average Rated Life (hr)	4000
Base	GU5.3 Bipin
Beam Angle (deg)	35
Beam Type	FL
Bulb	MR16
Centerbeam Candlepower (cp)	1500
Class	C (gas)
Color Rendering Index (CRI)	100
Color Temperature/CCT (K)	3000
Diameter (in)	2
Diameter (mm)	50.8
Ecologic	YES
Family Brand Name	TRU-AIM® BRILLIANT
Filament	AXIAL
Horizontal Beam Angle (deg)	35
Maximum Overall Length - MOL (in)	1.750
Maximum Overall Length - MOL (mm)	45.0
Nominal Voltage (V)	12.00
Nominal Wattage (W)	35.00
Vertical Beam Angle (deg)	35

**Additional Product Information**

**[Product Documents, Graphs, and Images](#)**

**[Packaging Information](#)**



**Footnotes**

- UV Filter capsule with axial filament in aluminized reflector.
- Max. seal temperature 370 C (662F)
- Max pin temperature 250 C.
- A protective shield must be used external to the lamp.

[Print Page](#)