



Product Number: 64733

Order Abbreviation: MP175/BU-ONLY/MED

General Description: 175W open fixture rated metal halide lamp, clear, base up burn within 15deg

Product Information

Abbrev. With Packaging Info.	MP175BUONLYMED 20/CS 1/SKU
ANSI Code	M57/O
Approx. Lumens (initial - vertical)	14400
Approx. Lumens (mean - vertical)	10800
Arc Length (in)	0.71
Arc Length (mm)	18
Average Rated Life - Vertical (hr)	10000
Avg Rated Life (hrs)	10000
Base	E26 Medium
Bulb	ED17
Color Rendering Index (CRI)	65
Color Temperature/CCT (K)	3600
Diameter (in)	2.126
Diameter (mm)	54.00
Family Brand Name	Metalarc Pro-Tech®
Fixture Requirement	O
Hot Restrike Time (min)	7-12
Lamp Finish	Clear
Light Center Length - LCL (in)	3.39
Light Center Length - LCL (mm)	86
Maximum Base Temperature - Fahrenheit	410
Maximum Base Temperature - Celsius	210
Maximum Bulb Temperature - Fahrenheit	752
Maximum Bulb Temperature - Celsius	400
Maximum Overall Length - MOL (in)	5.43
Maximum Overall Length - MOL (mm)	138
Nominal Voltage (V)	132.00
Nominal Wattage (W)	175.00
Operating Position	BASE UP WITHIN 15DEG ONLY
Warm-up Time (min)	2-4

Footnotes

- O = Lamps classified as O-type, comply with ANSI standard C78.389 for containment testing and may be used in open luminaries. See lamp warning.