



Time Switches



24 Hour Dial w/Skipper

The T1900 Supervisor Series provides up to 96 operations (48 ON /48 OFF) every 24 hours. This series provides operations with minimum ON / OFF times of 15 minutes. Trippers slide in and out of dial for fast accurate setting. The skipper models provide for operations to be omitted on selected day(s) of the week. Model with carryover provides a minimum of 16 hours of carryover to maintain preset schedules within +/- 2% accuracy during power failures. The carryover automatically rewinds when power resumes. Only one hour is required to rewind the carryover for each two hours of power outage.

Applications

- Oil Well Pumps
- Filters
- Blowers
- Poultry Feeders
- Heaters
- Process Equipment
- Recorded Music
- Dairy Equipment
- Fans
- Silo Unloaders
- Poultry Foggers

Specifications

Case – Drawn steel 7-3/4" (19.7 cm) High, 5" (12.7 cm) Wide, 3" (7.6 cm) Deep in gray finish. Spring hasp, with hole for lock, holds permanently attached, side hinged door closed. Three mounting holes on back plus handy box mounting holes.


Knockouts – Combination 1/2"-3/4" nominal knockouts, one on back and each side of case and two on bottom.

Optional Enclosures – See Time Switch Cases for optional enclosures.


Special Voltages and Cycles – See Time Switch Motors for available motors.

Switch Rating – 20 Amp maximum 125, 208-277 and 480 VAC; 1/2 HP , 125 VAC; 1 HP, 250 VAC


Power Input – 5 Watts maximum.



C22.2-177
LR3730
UL917



2.75 lbs
1.25 kg



-40°F
(-40°C)
to
130°F
(54°C)

Model #	MODEL # STEEL NEMA 3R CASE	Switch	Clock Motor Volts 60 Hz	Spring Wound Carryover	Amps	Skipper Wheel
T1905		SPDT	125	No	20	No
T1905E		SPDT	480	No	20	No
T1906		SPDT	208-277	No	20	No
T1975	T1975R	SPDT	125	No	20	Yes
T1976	T1976R	SPDT	208-277	No	20	Yes
T1975E	T1975ER	SPDT	480	No	20	Yes

*For additional trippers (12 per pack), order No. 156T1950A.
Replacement Snap Switch 133T701A.*