



Mechanical Controls



T2000R Series 60 Amp Pool/Spa Control Panels

The T2000R Series Control Panels feature an all-weather enclosure and contain a 4 circuit breaker base, an equipment grounding bar and a mechanical time switch mechanism. The circuit breaker base accepts interchangeable type breakers made by a number of different manufacturers. In addition, the enclosure has provision for installing additional switches or GFCI receptacles on the side and inside.

Applications

- Filter Pumps
- Lights
- Ventilating Systems
- Signs
- Air Conditioners
- Heaters

Specifications

Case – 16-3/4" (42.6 cm) H x 8-7/8" (22.5 cm) W x 4-3/8" (11.1 cm) D. 0.048" steel with electrostatically applied light beige finish.

Knockouts – Five combination 1/2"-3/4" and three 3/4" - 1" on the bottom, one combination 1/2"-3/4" on the left side, one 3/4"-1" on the back and one combination 1-3/4" x 2-3/4" knockout on the right side for mounting switches or GFCI

Panel Rating – 60 Amp 120/240 VAC or 120/208 VAC; Single Phase-60 Hz

Time Switch Rating – 30 Amp Resistive Inductive, Tungsten or 1000 VA pilot duty each pole 120/208/240 VAC; 2 HP (24 FLA) - 120 VAC; 5 HP (28 FLA) - 240 VAC

Shipping Weight – See table.

Agency Approval – CSA/C-US



T21000R



T21004R



T20004R

Model #	Description/Mechanism	Switch	Clock Supply Volts 60 Hz	Shipping Weight
T21000R	Enclosure only	None	NA	11.2 lbs (5.0 kg)
T21001R	T101M	SPST	120	14.0 lbs (6.3 kg)
T21004R	T104M	DPST	240	14.0 lbs (6.3 kg)
T20004R*	T104M	DPST	240	14.0 lbs (6.3 kg)

* T20004R has a limited availability, T21004R is the replacement model.
 For additional trippers (1 "ON" 1 "OFF" per pack), order No. 156T1978A
 For additional "OFF" trippers (25 "OFF" per pack), order No. PA115
 For Stand offs for décor knockouts (4 stand-offs per pack), order No. 21T156A