



PRODUCTS

PRODUCT DEVEL

|                          |
|--------------------------|
| Aquarium                 |
| AV/Photographic          |
| Cinema                   |
| Entertainment            |
| General Lighting         |
| Graphic Arts             |
| Heater/IR                |
| Horticulture             |
| Miniature                |
| Scientific-Medical       |
| Semiconductor            |
| UV                       |
| Lamp & Ballast Recycling |



[Products](#) > Product Data Specs - More Info.

## Product Data Specs - More Info.

USHIO Product Data Specs - More Info.



Lamp Photo



[Report broken links or errors](#)

[Share](#) |

Email this page to a friend

Enter email address

ushio.com/products/datasearch.htm

|                      |                           |
|----------------------|---------------------------|
| USHIO Code#          | 3000238                   |
| USHIO Lamp Series    | ULTRA CFL                 |
| Product ID/ANSI Code | CF26DE/865                |
| Description          | CF26DE/865, Double Tube   |
| Description 2        | 20W, 6500K, 85CPI, C21, 2 |

Enter email address

Send

**REQUEST FOR A QUOTE**  
**NEW SEARCH**

|                          |                                        |
|--------------------------|----------------------------------------|
| Description 2            | 26W 8500K 85CRI G24Q-3                 |
| Item Market              | General Illumination                   |
| Item Type                | Fluorescent                            |
| Item Prefix              | CFL                                    |
| Base                     | G24Q3                                  |
| Voltage                  | 105.0                                  |
| Wattage                  | 26.0                                   |
| Amperage                 | 0.325                                  |
| Burn Position            | ANY                                    |
| Bulb Shape               | T4D                                    |
| Bulb Finish              | INPHOS                                 |
| CRI                      | 85                                     |
| Color Temp (K)           | 6,500                                  |
| Arc Gap (mm)             | N/A                                    |
| Ballast                  | N/A                                    |
| Beam Angle               |                                        |
| Beam Spread              | N/A                                    |
| Candle Power (cd)        |                                        |
| Contact to Contact (mm)  | N/A                                    |
| Efficacy (lm/W)          | 65.8                                   |
| Filament                 | N/A                                    |
| Front Glass Cover        | NO                                     |
| Initial Lumens (lm)      | N/A                                    |
| Mean Lumens (lm)         | 1710                                   |
| Luminous Flux (lm)       | 1710                                   |
| Life (hr )               | 10,000                                 |
| Life Commercial (hr)     | 12500                                  |
| Diameter (mm )           | 12.70                                  |
| MOL (mm)                 | 165.00                                 |
| Light Center Length (mm) | N/A                                    |
| Lighted Length (lm)      | N/A                                    |
| Reflector Size (mm)      |                                        |
| Reflector Type           | N/A                                    |
| Working Distance (mm)    | N/A                                    |
| Spectral Range           | N/A                                    |
| Ozone Free               | YES                                    |
| UV Protected             | N/A                                    |
| Case Qty                 | 50                                     |
| Download brochure        | <a href="#">CompactFluorescent.pdf</a> |

[Back](#)

Data specs. are subject to change without prior notice.

[back to top](#)

Get Connected and follow us  
on Facebook and Twitter



[Product Lamps](#)  
[Power Supplies](#)  
[Product Catalog](#)  
[Product Data Specs. Search](#)  
[Annual Energy Savings / ROI](#)  
[Calculator](#)

[Press Releases](#)  
[News and Events](#)  
[Excimer Sources](#)  
[U-eLektron EBeam Sources](#)  
[Industry Systems & Apps](#)

[Lamp](#)  
[Lamp](#)  
[Our P](#)  
[Envirc](#)  
[FAQs](#)

©2011 USHIO America, Inc. All rights reserved.

(800) 838-7446 | [Privacy Policy](#)