

H6

6" Architectural Housing

Product Description

The H6 is a recessed housing for new construction designed to accommodate all 6" downlights from Cree LED Lighting. It is rated for use with the LR6 and CR6 families, ensuring the benefits of the low energy consumption are realized in the calculation of energy density for energy code compliance and LEED certification. The H6 is IC rated, airtight, inherently protected, and California Title-24 compliant when ordered with the GU24 socket.

Compatibility Information

H6-GU24

- LR6-GU24
- LR6C-GU24
- LE6-GU24
- LE6C-GU24
- LR6-DR Series(120V)
- CR6-GU24

H6-277V

- LR6-277V
- LR6C-277V
- LR6-DR Series (277V)

H6-277V US

- LR6-277V
- LR6C-277V
- LR6-DR Series (277V)

Ordering Information

- H6-GU24 - 6" Recessed Housing, 120V, GU24 base
- H6-277V - 6" Recessed Housing, 277V, 277V connector
- H6-277V US - 6" Recessed Housing, 277V, 277V connector, US manufacture

Product Information

- Recessed housing with integral nailer and ceiling grid attachment detail.
- Integral bar-hanger spans from 14" to 24 1/2".
- Dimensions h = 7 1/2", w = 7 1/2", l = 12 1/4".
- Accommodates ceiling thickness from 1/4" to 1 1/4".
- Suitable for insulated or non-insulated ceilings.
- Air-tight rated – tested in accordance with ASTM E283.
- Title-24 compliant when utilized with GU24 socket.
- Gasket on bottom of housing for seal between housing and ceiling material for Title-24 compliance.
- cULus Listed®. Suitable for damp locations.

