

G16.5

LED

2.5 Watt G16.5 Specifications



The ETi 2.5 watt 90 lumen G16.5 LED lamp offers exceptional performance for precision lighting applications, while reducing energy and maintenance cost when compared with conventional light sources. This G16.5 Lamp has E12 base and comes with medium adapter (E26). They are UL listed for use in damp and dry locations and are RoHS compliant with no lead or mercury. Ideal for accent lighting. Warranty period is 3 years or 36 months. Suitable for installations from - 4° F to 104° F.


KEY FEATURES & BENEFITS

- 2.5 Watt Low Power and High Performance
- 90 Lumen
- 83 CRI
- 3000K
- UL - Damp and Dry Locations
- Replaces most applications using 15w energy saving incandescent lamps
- Rated life 25,000 hours



This light source meets restrictions on hazardous substances.

LAMP DIMENSIONS



SKU# 52101211

Dimension A = 1.99"

Dimension B = 3.34"

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, please see www.etiled.us

APPLICATION INFORMATION

Chandeliers, bathroom vanity, accent lighting and general decorative indoor lighting in residential, office, retail, restaurant, school, hospital and hotel/motel locations.

ETI SOLID STATE™
LIGHTING
INC.

2.5 Watt G16.5

LED

SPECIFICATION DATA

Project _____

Item Number _____

Prepared by _____ Date _____

ORDERING INFORMATION

| Model Number | Description | Wattage | Base Type | Input Voltage (VAC) | Average Rated Life ¹ | Typical Lumens ² | CCT ³ | CBCP | Beam | R9 | DUV | CRI ⁴ | Power Factor | Operating Frequency |
|--|----------------------|---------|-----------|---------------------|---------------------------------|-----------------------------|------------------|------|------|----|--------|------------------|--------------|---------------------|
| 52101211 | G16.5 2.5 E12 E830NA | 2.5 | E12 | 120 | 25,000 | 90 | 3000K | 4.26 | 246° | 24 | 0.0006 | 83 | >0.5 | 60Hz |
| ¹ Hours lifetime with 70% lumen maintenance | | | | | | | | | | | | | | |
| ² Thermally stable typical lumens (±10%) | | | | | | | | | | | | | | |
| ³ Thermally stable CCT (±10%) | | | | | | | | | | | | | | |
| ⁴ Color rendering index/Ra | | | | | | | | | | | | | | |

SHIPPING INFORMATION

| Model Number | Item UPC | Item Dimensions (H x L x W) | Item Weight (lbs) | Inner Pack Qty | Inner Carton Bar Code | Inner Carton Dimensions (H x L x W) | Inner Pack Weight (lbs) | Master Pack Qty | Master Carton Bar Code | Master Dimensions (H x L x W) | Master Pack Weight (lbs) |
|--------------|---------------|-----------------------------|-------------------|----------------|-----------------------|-------------------------------------|-------------------------|-----------------|------------------------|-------------------------------|--------------------------|
| 52101211 | 836607 006400 | 5" x 2.2" x 2.2" | 0.16 | 12 | 30836607 006401 | 5.2" x 12.2" x 7" | 2.2 | 48 | 50836607 006405 | 10.9" x 14.6" x 12.7" | 10 |

