



**EYE LIGHTING INTERNATIONAL
OF NORTH AMERICA, INC.**
A SUBSIDIARY OF IWASAKI ELECTRIC CO., LTD.

Home About Us Products How to buy Trade Shows Trade Associations Industry Links Lighting FAQs Lighting Library

Single-Ended

JD Series - 220-250V Mini-Candelabra Base & DC Bayonet Base

Features

- Crisp, white light
- Mini-Candelabra, DC Bayonet, Medium and European Bases
- 28V, 30V, 110V, 120V, 130V, 220-230V and 240-250V types
- From 50W to 500W

Applications

- Home
- Retail Stores
- Lounges
- Furniture
- Museums
- Restaurants
- Offices
- Displays
- Supermarkets

220-250V Mini-Candelabra Base & DC Bayonet Base														
Watts	Volts	Base	Product	Product	Product	Case	Initial Lumens	Average Life Hours	Color Temp. (K)	Filament	M.O.L.		L.C.L.	
(W)	(V)		Code	Description	Comparison	Qty	(lm)				(in.)	(mm)	(in.)	(mm)
100	220	Mini-Can	85490	JD220/230V 100W/M2	100Q/CL/MC/220-230V	50	1400	1500	2850	CC-13	3.15	80	2.16	55
	230	DC-Bay	85487	JD220/230V 100W/BD	100Q/CL/DC/220-230V	50	1400	1500	2850	CC-13	3.43	87	2.16	55
	240 250	DC-Bay	85669	JD240/250V 100W/BD	100Q/CL/DC/240-250V	50	1400	1500	2850	CC-13	3.43	87	2.16	55
150	220	Mini-Can	85559	JD220/230V 150W/M2	150Q/CL/MC/220-230V	50	2250	1500	2900	CC-13	3.15	80	2.16	55
	230	DC-Bay	85510	JD220/230V 150W/BD	150Q/CL/DC/220-230V	50	2250	1500	2900	CC-13	3.43	87	2.16	55
	240	Mini-Can	85693	JD240/250V 150W/M2	150Q/CL/MC/240-250V	50	2250	1500	2900	CC-13	3.15	80	2.16	55
	250	DC-Bay	85681	JD240/250V 150W/BD	150Q/CL/DC/240-250V	50	2250	1500	2900	CC-13	3.43	87	2.16	55
250	220	Mini-Can	85608	JD220/230V 250W/M2	250Q/CL/MC/220-230V	50	4500	2000	2900	CC-8	3.19	81	2.40	61
	230	DC-Bay	85567	JD220/230V 250W/BD	250Q/CL/DC/220-230V	50	4500	2000	2900	CC-8	2.95	75	1.65	42
	240	Mini-Can	85610	JD240/250V 250W/M2	250Q/CL/MC/240-250V	50	4500	2000	2900	CC-8	3.19	81	2.40	61
	250	DC-Bay	85705	JD240/250V 250W/BD	250Q/CL/DC/240-250V	50	4500	2000	2900	CC-8	2.95	75	1.65	42
500	220	Mini-Can	85657	JD220/230V 500W/M2	500Q/CL/MC/220-230V	50	9500	2000	2950	CC-8	3.74	95	2.60	66
	240	Mini-Can	85630	JD240/250V 500W/M2	500Q/CL/MC/240-250V	50	9500	2000	2950	CC-8	3.74	95	2.60	66
	250	DC-Bay	85622	JD240/250V 500W/BD	500Q/CL/DC/240-250V	50	9500	2000	2950	CC-8	3.54	90	1.90	48

Burning Position: Universal

--top--