



## WORLDWIDE PARTNER

Commercial Products & Solutions

→ HOME **PRODUCTS** ▶ EDUCATION / RESOURCES LIGHTING APPLICATIONS SITE SEARCH

Where to Buy | FAQs | Contact Us | EliteNet

PRINT

<u>Products</u> > 16099

## 16099 - FLE5/2/CAM/827

GE Soft White B13 - Facilities; Retail Display; Hospitality; Office; Restaurant











View Larger

## **GENERAL CHARACTERISTICS**

CENERAL CHARACTERIOTICS		
Lamp type	Compact Fluorescent - Self- Ballasted	
Bulb	B13	
Base	Medium Screw (E26)	
Wattage	5	
Voltage	120	
Rated Life	6000 hrs	
Starting Temperature (MIN)	-15 ℃ (5 ℉)	
Total Harmonic Distortion (THD)	145 %	
Picograms of Mercury	3646 picograms	
Primary Application	Chandelier; Facilities; Retail Display; Hospitality; Office; Restaurant	

# PHOTOMETRIC CHARACTERISTICS

Initial Lumens	200
Mean Lumens	160
Nominal Initial Lumens per Watt	40
Color Temperature	2700 K
Color Rendering Index (CRI)	82

## **ELECTRICAL CHARACTERISTICS**

Input Voltage	120 V	
Input Current	0.0850 A	
Power Factor	0.6	

# **DIMENSIONS**

Maximum Overall Length (MOL)	4.8000 in (121.9 mm)
Nominal Length	4.800 in (121.9 mm)

#### PRODUCT INFORMATION

## **ADDITIONAL RESOURCES**

# **Catalogs Testimonials**

**Brochures Product Brochures** 

Compact Fluorescent Lamps

**Disposal Policies & Recycling Information** 

Product Code	16099
Description	FLE5/2/CAM/827
Standard Package	Case
Standard Package GTIN	10043168160992
Standard Package Quantity	10
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	10
UPC	043168160995

# **A** CAUTIONS & WARNINGS

See list of cautions & warnings.

# NOTES

- Fluorescent lamp lumens decline during life
- Lumens on one piece self ballasted lamp systems are measured base up.
- Use only on 120V 60 Hz circuits. Do not use on dimming circuits, photocells or timers. Do not use in wet locations.

Return To Top

Home | Products | EliteNet | Education/Resources | Lighting Applications | Where to Buy | FAQs | Contact Us | Site Map
Products for Your Home | Press Room | Corporate | Investor Information | Privacy Policy | Accessibility Statement | Terms of Use
Copyright General Electric Company 1997-2008