

EnhanceLite™ PAR30-L

High output, Long Neck PAR30 LED Lamp



EnhanceLite® PAR30 - Long Neck

Key Product Features

- High output PAR30 LED lamp
- Excellent color rendering
- Exceptional light distribution
- Enhanced passive cooling system allows for reduced junction temperatures, extending the life of the lamp
- Environmentally Friendly – No mercury, No lead & RoHS Compliant
- Maintenance free - Long life operation
- Integrated high efficiency driver
- Complies with ANSI standard PAR30 Long Neck form factor
- All lamps are TÜV certified and tested to UL 1993, UL 8750 and are FCC certified
- No UV or IR radiation & No heat emitted in direction of light
- 5 year warranty

Specification Data

CCT (K)	Beam Angle	Power (W)	Lumens (lm)	CBCP (cd)	Efficacy (lm/W)	CRI	Voltage	Base Type	Life (hrs)	Weight	Dimmable	Model No.
2700K Incandescent White	27°	7.9	490	1,690	62	83	90-135 VAC, 60Hz	E26	50,000	10.0 oz (0.28 kg)	YES	LED-PAR30L-50-1XD-INF
		14.3	750	2,600	52							LED-PAR30L-75-1XD-INF
	35°	7.9	474	1,066	60							LED-PAR30L-50-1XD-IF
		14.3	740	1,680	52							LED-PAR30L-75-1XD-IF
	55°	7.9	470	487	60							LED-PAR30L-50-1XD-IWF
		14.3	720	745	50							LED-PAR30L-75-1XD-IWF
3000K Warm White	27°	7.9	490	1,690	62	83	90-135 VAC, 60Hz	E26	50,000	10.0 oz (0.28 kg)	YES	LED-PAR30L-50-1WD-INF
		14.3	750	2,600	52							LED-PAR30L-75-1WD-INF
	35°	7.9	474	1,066	60							LED-PAR30L-50-1WD-IF
		14.3	740	1,680	52							LED-PAR30L-75-1WD-IF
	55°	7.9	470	487	60							LED-PAR30L-50-1WD-IWF
		14.3	720	745	50							LED-PAR30L-75-1WD-IWF
4000K Cool White	27°	7.9	568	1,960	72	80	90-135 VAC, 60Hz	E26	50,000	10.0 oz (0.28 kg)	YES	LED-PAR30L-50-1CD-INF
		14.3	870	3,016	61							LED-PAR30L-75-1CD-INF
	35°	7.9	550	1,237	70							LED-PAR30L-50-1CD-IF
		14.3	858	1,949	60							LED-PAR30L-75-1CD-IF
	55°	7.9	546	565	69							LED-PAR30L-50-1CD-IWF
		14.3	835	864	58							LED-PAR30L-75-1CD-IWF

LEDnovation lamp models are tested for photometric performance in accredited third-party labs according to IES LM-79 requirements, with most reports available online at www.lednovation.com

DESIGNED AND MANUFACTURED IN THE USA

TESTED TO:
UL1993 & UL8750



CERTIFICATION NUMBER:
U8 10 09 71814 003

LEDnovation, Inc.