

LED Low Bay/Site Utility Series



Stock No.	Product Description
LED-8025-DL	GL-120/277-52-54-DL (Daylight) Utility Light
LED-8025-NW	GL-120/277-52-54-NW (Neutral White) Utility Light

Description:

Fully encapsulated, 120/277 Volt, E26 medium base mounting that integrates energy saving LED technology into a powerful yet energy saving SMD low bay/utility lamp. Available in Daylight (DL) or Neutral White (NW).

- 52 Watts
- 120 - 277 Volt operation
- Daylight DL (5700K), Neutral White NW (3000K)
- Lumens: 3200(DL), 3100(NW)
- 54 on-board SMD LEDs
- Up to 50,000 hour lamp life
- Operating range: -30C to 50C
- Not Dimmable
- 5 year warranty (see www.led-llc.com for full details)
- Patented under 29/415,685
- UL Listed Damp Location
- LM79, IES available
- Active Cooling Delta 70K Hr Fan

Applications:



LED Low Bay/Site Utility Series lamps can impact energy usage and costs in a major way for communities and housing developments with minimal to no maintenance costs thanks to the up to 50,000 hour lamp life.

- Site / Roadway / Post Top
- Security lighting
- Parks and quads
- Municipal lighting
- Parking Garage
- Low Bay Applications

NOTE: When retrofitting LED to HID fixture, ballast must be bypassed when present. Eliminating the ballast saves additional costs related to maintenance, energy consumption and performance. Additionally, by-passing ballast will insure no RFI interference.

Packaging:

Master-pack: 4 each



Technical Specifications:

Note: All specification information falls within a $\pm 2\%$ range and is subject to change

Bulb Type:	Site/Warehouse	Mounting:	E26 Medium Base
Bulb Material:	Alum/Polycarbon	Replaces:	175W MH
UV:	None	Life Time:	Up to 50,000 Hrs.
Output Power:	52W	Input Voltage:	AC 120 – 277V
Lumens:	3200(DL) 3100(NW)	Beam Angle:	360 °
Dimensions:	7-7/8" x 5-7/8" 200mm x 149mm	Kelvin Temp:	(DL) 5700K (NW) 3000K
Lumen per Watt:	60	LEDs:	54 SMD LEDs
Power Factor:	98	Mercury:	No
CRI:	81	Freq:	50-60Hz

without notice.

NOTE: Light Efficient Design is providing this information to the general public. Please note that all products contained herein are trademarked, copyrighted, and/or have patents pending. Any use of these designs is strictly prohibited without prior written consent. Light Efficient Design protects its proprietary information vigorously in the courts of the United States of America.

106 S. Wynstone Park Drive • N. Barrington, IL 60010
(847) 380-3540 • FAX: (847) 380-3542
www.led-llc.com



Light Efficient Design
a division of TADD, LLC