LED-8028 Post Top / Bollard / Site


Stock No. LED-8028-NW LED-8028-DL **Product Description**

PT-120/277-21-40-NW (3000K) PT-120/277-21-40-DL (5700K) 21w = 100W MH/HPS

Description:

LED retrofit design to replace MH and HPS lamps up to 100w. Fully encapsulated, 21 watt LED with E26 Edison base. Small, compact size allows placement in smaller bollards and other HID fixtures. Suitable for fully enclosed fixtures.

- 21W power consumption
- Replaces up to a 100W HID
- 360° illumination
- 120-277VAC, Non-Dimmable
- Available in 3000K or 5700K CCT
- >80 CRI
- 50,000 hr. rated L70 LED life
- Operating temp: -40°F 122°F
- UL Listed Damp (US & CA)
- 5 Year warranty



Applications:

LED Post top / Bollard / Site LED for HID retrofit lamps lower energy costs, bulb and ballast replacement costs and also can greatly reduce costly equipment rental when relamping HID lamps on and off cycle. LED for HID retrofits will also eliminate lamp disposal issues due to the mercury content in many HID lamps.

- · Outdoor area lighting
- Wall Pack
- Cold display
- Security Lighting

Packaging: 9/Master Carton

Unit: 4.7" x 4.7" x 8.9" Master: 14.8" x 14.8" x 9.5"

Note: When retrofitting LED to HID fixture, ballast must be by-passed when present. Eliminating the ballast saves additional costs related to maintenance, energy consumption and performance. Additionally, by-passing ballast will insure no RFI interference.



| Technical Specifications | | | |
|--------------------------|----------------------------------|--------------------------|----------------------------------|
| Bulb Type | HID Retrofit | Mounting | E26 |
| Bulb Material | Aluminum/ Polycarbonate | LEDs: | 40 Samsung #5630 SMD LED's |
| Power Consumption | 21 watts | Beam Angle | 360 ° |
| Lumens | 3000K: 1500 Lm 5700K: 1600 Lm | Dimmable | No |
| Efficacy | 73/80 Lumens / watt | Replaces | Up to 100W HID |
| Rated LED Life | Up to 50,000 Hrs. | сст | 3000К 5700К |
| Power Factor: | >99 | CRI: | > 80 |
| IR / UV | None | Mercury/ Lead Content | None |
| Warranty | 5 year Limited | Dimensions | 3.15" X 6.61" |

Note: All specification information falls within a \pm 2% range and is subject to change without notice.

to maintenance, energy consumption and performance. Additionally, by-passing ballast will insure no RFI interference.

NOTE: Light Efficient Design is providing this information to the general public. Please note that all products contained herein are trademarked, copyrighted, and/or have patents pending. Any use of these designs is strictly prohibited without prior written consent. Light interference.

Efficient Design protects its proprietary information vigorously in the courts of the United States of America.

106 S. Wynstone Park Drive • N. Barrington, IL 60010 (847) 380-3540 • FAX: (847) 380-3542

www.led-llc.com