

iPAR™-30L

Fixed Wattage



iPAR™-30L



PRODUCT SUMMARY

- Fixed Wattage
- Non-Dimmable
- 3 Color Temperatures
- Multiple Beam Spreads, Custom Optics
- Proprietary CrimpFin™ Heatsink Design
- 50,000 hour life, 5 year warranty
- Halogen PAR form factor (ANSI compliant)
- No UV or IR radiation
- Voltage: 120VAC
- 0.9 Power Factor
- Socket Type: Medium Screw Base
- Environment: Dry
- Length: 4.6 in, 117 mm
- Diameter: 3.75 in, 95 mm
- Weight: 0.75 lbs, 340 g

The iPAR™-30L lamps from MSi are fixed wattage LED replacement bulbs with the light output of incandescent sources. The lamps bring the innovation and experience from multiple engineering disciplines to deliver a solution that is optimal for commercial, retail and residential applications.

120~



2700K

3000K

4300K



Catalog#	Power	CCT (K)	CRI	Beam Spread	FWHM	Lumens	CBCP
iPAR30L27101N	12 W	2700	82	10°	8°	600	16,500
iPAR30L27161N			82	16°	13°		6,400
iPAR30L27221N			82	22°	15°		4,300
iPAR30L30101N	12 W	3000	82	10°	8°	650	17,500
iPAR30L30161N			82	16°	13°		6,700
iPAR30L30221N			82	22°	15°		4,500
iPAR30L43101N	12 W	4300	75	10°	8°	700	18,400
iPAR30L43161N			75	16°	13°		7,000
iPAR30L43221N			75	22°	15°		4,700

1342 South Powerline Road, Deerfield Beach, FL 33442

Toll Free 888.778.9864 | Fax Orders to: 954-971-3725 | info@msissl.com | www.msissl.com

iPAR-30L™



CANDELA DISTRIBUTION

BEAM DISTRIBUTION

0° AIMING FOOTCANDLES

10°



3000K



Distance To Floor	Beam Diameter (50% CBCP)	Footcandles On Floor (12 W)
5'	0.7'	700
10'	1.4'	175
15'	2.1'	78
20'	2.8'	44

16°



3000K



Distance To Floor	Beam Diameter (50% CBCP)	Footcandles On Floor (12 W)
5'	1.1'	268
10'	2.3'	67
15'	3.4'	30
20'	4.6'	17

22°

3000K



Distance To Floor	Beam Diameter (50% CBCP)	Footcandles On Floor (12 W)
5'	1.3'	180
10'	2.6'	45
15'	3.9'	20
20'	5.3'	11

CAUTION: Risk of electric shock. Do not open - no user serviceable parts inside. Use in dry locations only. Turn power off before inspection, installation, or removal. Not intended for use with emergency exit fixtures or emergency exit lights. Not for use where exposed to the weather. Not for use in completely enclosed fixtures. Use only on 120 Volts, 60 Hz circuits. Added weight of the device may cause instability of a free-standing portable luminaire.

WARRANTY: This product is covered by a 5 year limited warranty under normal operating conditions based on 12 hours of usage per day. For details please visit www.msissl.com/warranty.html.

1342 South Powerline Road, Deerfield Beach, FL 33442

Toll Free 888.778.9864 | Fax Orders to: 954-971-3725 | info@msissl.com | www.msissl.com