


**NS-42 / NS-43 / NS-44
NS-46 / NS-52 / NS-53
Reflector with Ring**

Type
Project
Catalog No.
Lamp/Wattage

TRIM DIMENSIONS



Trim OD: 5"
Aperture: 3-1/2"
Height: 2"

FEATURES

Trim
Precision spun 0.050 aluminum high grade reflector. Separate trim ring available in metal, may also be used with custom combination of plastic or metal ring finishes.

Mounting
Trim includes three trim clips that securely mount trim in housing.

Compatible Housings
Compatible with Line Voltage, Compact Fluorescent, and GU24 Compact Fluorescent housings. See individual specification sheets for more information.

Lamp
Line Voltage
50W R20/PAR20 Max. (NS-401QAT; NSIC-401QAT; NSR-404QAT)
Compact Fluorescent
13W Quad/Triple (NS-406Q; NS-406EL; NSR-408Q; NSR-408EL)
GU24 Compact Fluorescent
13W-26W GU24 (NHRIC-4G24AT, NHRIC-4G24AT)

Labels and Listings
cULus Listed for Damp Location when used with compatible housing.

Reflector with Ring

- NS-42:** Specular Gold Reflector with White Metal Ring
- NS-42G:** Specular Gold Reflector with Gold Metal Ring
- NS-43:** Specular Black Reflector with White Metal Ring
- NS-43B:** Specular Black Reflector with Black Metal Ring
- NS-44:** Specular Clear Reflector with White Metal Ring
- NS-44C:** Specular Clear Reflector with Chrome Metal Ring
- NS-44HZ:** Haze Reflector with White Metal Ring
- NS-44N:** Specular Clear Reflector with Natural Metal Ring
- NS-46:** Specular White Reflector with White Metal Ring
- NS-52:** Natural Metal Reflector with Natural Metal Ring
- NS-53:** Copper Reflector with Copper Metal Ring
- NS-53BZ:** Bronze Reflector with Bronze Metal Ring

Compatible Housings

LINE VOLTAGE			
Item Number	Installation Type	Lamp	Dimensions
<input type="checkbox"/> NS-401QAT	Non-IC Air-Tight New Const.	50W R/PAR20	W: 5-5/8" L: 8-1/2" H: 5-5/8"
<input type="checkbox"/> NSIC-401QAT	IC Air-Tight New Construction	50W R/PAR20	W: 5-1/4" L: 8-1/2" H: 6-3/8"
<input type="checkbox"/> NSR-404QAT	Non-IC Air-Tight Remodel	50W R/PAR20	W: 4-1/4" L: 11-1/4" H: 5-5/8"
COMPACT FLUORESCENT			
<input type="checkbox"/> NS-406Q	Non-IC New Constr., Magnetic	13W Quad	W: 6-1/4" L: 10" H: 5-1/2"
<input type="checkbox"/> NS-406EL	Non-IC New Constr., Electronic	13W Quad/Triple	W: 6-1/4" L: 9" H: 5-1/2"
<input type="checkbox"/> NSR-408Q	Non-IC Remodel, Magnetic	13W Quad	W: 4-3/4" L: 11-7/8" H: 5-1/2"
<input type="checkbox"/> NSR-408EL	Non-IC Remodel, Electronic	13W Quad/Triple	W: 4-3/4" L: 11-7/8" H: 5-1/2"
GU24 COMPACT FLUORESCENT			
<input type="checkbox"/> NHRIC-4G24AT	IC Air-Tight New Construction	13W-26W GU24	W: 6-1/4" L: 13-1/4" H: 6-3/8"
<input type="checkbox"/> NHRIC-4G24AT	IC Air-Tight Remodel Housing	13W-26W GU24	W: 4-1/4" L: 13" H: 6-3/8"