

Type

Project

Catalog No.

Lamp/Wattage

**NTH-119****Roundback Universal Lamp Holder**Lamp: 50W R20/PAR20 / 75W BR30/PAR30  
250W PAR38 / 300W BR40**PRODUCT DESCRIPTION**

Line voltage cylindrical housing, roundback design. Structural arm provides full adjustment of light source for special aiming and completely conceals wire lead from socket to contact head. Internal mechanism allows for adjustment and resists angle degradation. Adjustment knob on housing side allows user to extend or retract the neck of the lamp source.

**FEATURES**

- Deep drawn solid round back steel housing for high strength and rigidity
- Adjustable socket
- Completely concealed wiring
- Fully adjustable, firm angle position
- High-strength stainless steel electrical contacts
- One or two circuit track capable

**CONSTRUCTION****Housing**

0.030" Deep drawn steel construction with simple aesthetic design. All edges are softened for aesthetic appearance. Groove and tightening knob on housing side allow user to adjust lamp position.

**Structural Arm**

Extruded 0.055" aluminum arm connects fixture housing to electrical contact head. Internal tightening mechanism maintains desired lamp aiming angles. Structural arm also functions as wire way, completely concealing lead wire from socket to contact head.

**Socket**

Porcelain jacketed aluminum screw thread medium-base socket.

**Lamp**

50W R20/PAR20 Maximum (not included)  
75W BR30/PAR30 Maximum (not included)  
250W PAR38 Maximum (not included)  
300W BR40 Maximum (not included)

**Contact Head Assembly**

"H" Style (standard): Three 0.030 stainless steel contacts mounted in premium plastic housing.

"J" Style: Two contacts and ground contact mounted in premium plastic housing with on/off switch.

"L" Style: Two contacts and ground contact mounted in premium plastic housing.

**Finishes**

Black, Silver, or White heat rated baked enamel paint. Custom painting or anodizing for special applications are also available. Custom finishes will require lead times that vary depending on vendor schedule. Please consult factor for quotation, and provide either a Dunn Edwards number or color chip for exact matching.

**One/Two Circuit Conversion**

Positive contact (opposite neutral and ground contacts) is preset to "down" position at the factory, but may be raised to the high position to install onto the second circuit of Nora Lighting's NT-2300 series two-circuit track.

**Compatibility**

H-Style is compatible with Halo or any other brands configured to Halo 3 (single circuit) or Halo 4 (2 circuit) track system design.


J-Style is compatible with "J" Style track.

L-Style is compatible with "L" Style track.

*Note: fixtures may not be compatible with non-Nora monopoint adapters.*

**Listing**

UL Listed as track lighting fitting

**ITEM NUMBERS****NTH-119 Dimensions:**

Diameter: 2-1/8"  
Length: 5-3/8"  
Max. Ext.: 8-7/8"

*Note: All dimensions are given without lamp installed and vary depending on lamp.*

**NTH-119B:** Black Roundback Universal Lamp Holder, H-Style

**NTH-119B/J:** Black Roundback Universal Lamp Holder, J-Style

**NTH-119B/L:** Black Roundback Universal Lamp Holder, L-Style

**NTH-119S:** Silver Roundback Universal Lamp Holder, H-Style

**NTH-119S/J:** Silver Roundback Universal Lamp Holder, J-Style

**NTH-119S/L:** Silver Roundback Universal Lamp Holder, L-Style

**NTH-119W:** White Roundback Universal Lamp Holder, H-Style

**NTH-119W/J:** White Roundback Universal Lamp Holder, J-Style

**NTH-119W/L:** White Roundback Universal Lamp Holder, L-Style