



Switch Start Metal Halide Protected

Switch Start MH Protected 400W/635 EX39 ED37 CO

PHILIPS
sense and simplicity

Switch Start Metal Halide Protected

Product data

• Product Data

Product number	133330
Full product name	Switch Start MH Protected 400W/ 635 EX39 ED37 CO
Short product name	Switch St MH Prot 400W/635 EX39 ED37 CO
Pieces per Sku	1
Skus/Case	6
Bar code on pack	046677133306
Bar code on case	50046677133301
Logistics code(s)	928601119601

• General Characteristics

Base	Exclusionary Mogul Screw [Exclusionary Mogul Screw]
Base Information	Nic/Brass [Nickel/Brass Base]
Bulb	ED37
Bulb Material	Hard Glass
Bulb Finish	Coated
Operating Position	Base Up +/-15D [Hanging +/-15D or Base Up (BU)]
Main Application	General Lighting
RatedAvgLife(See Family Notes)	20000 hr
Energy Saving	Not Applicable

• Electrical Characteristics

Watts	400 W
Lamp Voltage	135 V
Lamp Current	3.25 A
Ignition Time	120 s
Re-ignition Time [min]	15 min

• Environmental Characteristics

Mercury (Hg) Content	65 mg
-------------------------	-------

• Light Technical Characteristics

Color Code	635 [CCT of 3500K]
Color Rendering Index	67 Ra8
Color Designation	White
Color Temperature	3700 K
Color Temperature technical	3700 K
Chromaticity Coord- inate X	395 -
Chromaticity Coord- inate Y	400 -
Initial Lumens	34500 Lm
Luminous Efficacy Lamp	86 Lm/W
Design Mean Lumens	22425 Lm


• Product Dimensions

Light Center Length L	7 in
Max Overall Length (MOL) - C	11.5 in
Diameter D	4.625 in

• Luminaire Design Requirements

Cap-Base Tempera- ture	210 C
Bulb Temperature	400 C

Dimensional drawing



© 2010 Koninklijke Philips Electronics N.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com/lighting

2010, November 23
data subject to change