

PAR30L

75W 130V PAR30L WFL 40D 1CT

Philips Halogen PAR lamps will provide bright, white light across the product line and feature excellent beam qualities for accent or ambient lighting. Their optimized coil and burner design allows for clear, crisp lighting effects with excellent color rendering, making it easy to optimize the look and feel of your store and your merchandise.

Product data

• General Characteristics

Index Base Medium [Single Contact Medium Screw] Base Information Brass [Brass Base] PAR30L [PAR 3.75 inch/95mm Long] Bulb 120V **Bulb Material** Hard Glass Approx **Bulb Finish** Clear MBCP@120v Reflector Finish Aluminized

Filament Shape CC-8 [Axial] Operating Position Universal [Any or Universal (U)] Indoor Reflector

Main Application Atmosphere Gas 2500 hr

RatedAvgLife(See Family Notes)

5000 hr Rated Avg. Life @

120v **Estimated Energy** 9.03 \$ Cost/YR Life with 3h/day use 2.3 an

[years]

• Electrical Characteristics

Energy Used 75 W Voltage 130 V

• Light Technical Characteristics

Beam Description Wide Flood Beam Angle 40 D Approx. MBCP 1750 cd

100 Ra8 Color Rendering 2870 K Color Temperature Lumens (Brightness) 1005 Lm Initial Lumens @ 780 Lm 1400 cd

• Product Dimensions

Max. Overall Length 4.5 (max) in (MOL) - C Diameter D 3.75 in

• Product Data

924757100706 Order code Full product code 924757100706 Full product name 75W 130V PAR30L WFL 40D 1CT 75W 130V PAR30L WFL 40D 1CT Order product name Pieces per pack Packing configuration 15 Packs per outerbox 15 46677229450 Bar code on pack -EAN1

50046677229455 Bar code on outerbox - EAN3

Logistic code(s) -924757100706

Net weight per piece 0.001 kg



Dimensional drawing







 $\ensuremath{\textcircled{\odot}}$ 2011 Koninklijke Philips Electronics N.V. All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.