

## Mercury Vapor 100W Med A23 CO

Product family description Long life high intensity discharge mercury lamps.

## Features/Benefits

- 24,000 hour rated average life for reduced cost of lamp maintenance.
- · Wide range of lamp types for indoor and outdoor use.
- Universal operating position.

## **Applications**

• Ideal for sign lighting, security lighting and roadway lighting.

## Notes

- Rated average life is the life obtained, on the average, from large representative groups of lamps in laboratory tests under controlled conditions at 10 or more operating hours per start. It is based on survival of at least 50% of the lamps and allows for individual lamps or groups of lamps to vary considerably from the average. For lamps with a rated average life of 24,000 hours, life is based on survival of 67% of the lamps. (351)
- Approximate lumen values listed are for vertical operation of the lamp. (352)
- Means Lumens is the approximate lumen output at 40% of lamp rated average life. (353)
- Heat resisting glass bulb.

Product data		
Product Number	356584	
Full product name	Mercury Vapor 100W Med A23 CO	
Ordering Code	H38MP-100/DX	
Pack type	1 Sleeve Open End	
Pieces per Sku	1	
Skus/Case	24	
Pack UPC	046677356583	
EAN2US		
Case Bar Code	50046677356588	
Successor Product number		
Base	Medium [Single Contact Medium Screw]	
Base Information	Brass [Brass Base]	



Product data		
Bulb	A23	
Bulb Material	Hard Glass	
Bulb Finish	Coated	
Operating Position	Universal [Any or Universal (U)]	
Packing Type	1SL [1 Sleeve Open End]	
Packing Configuration	24	
Ordering Code	H38MP-100/DX	
Pack UPC	046677356583	
Case Bar Code	50046677356588	
Rated Avg. Life	24000 hr	
ANSI Code HID	H38	
Watts	100W	
Lamp Voltage	130 V	
Color Rendering Index	45 Ra8	
Color Temperature	3700 K	
Initial Lumens	4400 Lm	
Design Mean Lumens	3700 Lm	
Light Center Length L	3.5 in	
Max Overall Length (MOL) - C	5.438 in	
Diameter D	2.875 in	
Product Number	356584	





Mercury Vapor A23 CO



Base Medium







Mercury Vapor A23

Operating Position Universal

