

FB34T12/6 WW EW ALTO

Product family description T12 Medium Bi-Pin Fluorescent Lamps.

Features/Benefits

· 6 inch leg spacing.

Notes

- Rated average life under specified test conditions with lamps turned off and restarted no more frequently than once every 3 operating hours. Lamp life is appreciably longer if lamps are started less frequently. (202)
- Approximate Initial Lumens. The lamp lumen output is based upon lamp performance after 100 hours of operating life, when the output is measured during operation on a reference ballast under standard laboratory conditions. (203)
- For expected lamp lumen output, commercial ballast manufacturers can advise the appropriate Ballast Factor for each of their ballasts when they are informed of the designated lamp. The Ballast Factor is a multiplier applied to the designated lamp lumen output. (204)
- Design Lumens are the approximate lamp lumen output at 40% of the lamp's Rated Average Life. This output is based upon measurements obtained during lamp operation on a reference ballast under standard laboratory conditions. (208)


Product data	
Product Number	378620
Full product name	FB34T12/6 WW EW ALTO
Ordering Code	FB34/WW/6/EW/ALTO
Pack type	1 Lamp
Pieces per Sku	1
Skus/Case	12
Pack UPC	046677378622
EAN2US	
Case Bar Code	50046677378627
Successor Product number	
Base	Medium Bi-Pin [Medium Bi-Pin Fluorescent]
Base Information	Green Base
Bulb	T12-6U [U-bent T 12/8 inch with 6" spacing]
Execution	Econ-o-watt
Packing Type	1LP [1 Lamp]
Packing Configuration	12



Product data	
FB34T12/6	
ALTO®	
18000 hr	
FB34/WW/6/EW/ALTO	
046677378622	
50046677378627	
Not Applicable	
34W	
29	
53 Ra8	
Warm White	
3000 K	
2400 Lm	
2050 Lm	
22.44	
378620	




F-T12-UR Med Bipin/GB



Base Medium Bi-Pin





F-T12-UR Med Bipin

