Ceramalux® Non-ALTO

Ceramalux S76 35W BD17 CL 1CT

Replace yellow light with crisp, bright white light with just a simple twist! Ideal for industrial applications, warehouses, post top applications and parking lots.

Product data

• General Characteristics

Base	Medium [Single Contact Medium Screw]
Base Information	Brass [Brass Base]
Bulb	BD17
Bulb Material	Hard Glass
Bulb Finish	Clear
Operating Position	Universal [Any or Universal (U)]
Main Application	General Lighting
Rated Avg. Life	24000 hr

• Electrical Characteristics

Energy Used	35 W
Lamp Voltage	55 V
Lamp Current	0.83 A
Ignition Time	5 (max) s
Re-ignition Time [min]	5 (max) min

• Environmental Characteristics

Mercury (Hg) Content	31.9 (max) mg

• Light Technical Characteristics

Color Rendering Index	21 Ra8
Color Temperature	2100 K
Color Temperature technical	1900 K
Chromaticity Coordinate X	537 -
Chromaticity Coordinate Y	420 -
Initial Lumens	2300 Lm
Luminous Efficacy Lamp	66 Lm/W
Lumen Maintenance EM 10000h	93 %
Design Mean Lumens	2025 Lm
Lumen Maintenance 20000h	82 %

• UV-related Characteristics

• Product Dimensions

Light Center Length L	3.438 in
Max. Overall Length (MOL) - C	5.438 (max) in
Diameter D	2.125 in

• Luminaire Design Requirements

Cap-Base Temperature	190 (max) C
Bulb Temperature	400 (max) C

• Product Data

Order code	928601144311
Full product code	928601144311
Full product name	Ceramalux S76 35W BD17 CL 1CT
Order product name	Ceramalx S76 35W BD17 CL 1CT
Pieces per pack	1
Packing configuration	12
Packs per outerbox	12
Bar code on pack - EAN1	46677409791

PHILIPS

sense and simplicity

Ceramalux® Non-ALTO

Bar code on outerbox - EAN3	50046677409796	Net weight per piece	0.010 kg
Logistic code(s) - 12NC	928601144311		

Dimensional drawing

Product	C (Max)	D (Norm)
HPS R 35W E26 BD17 U	5.438	2.125

www.philips.com/lighting

2011, July 27
data subject to change