# MH400/ED37/U/4K

# **GENERAL Characteristics**

Lamp Type	Standard MH Single End
ANSI Code	M59/E
Bulb Shape	ED37
Base Type	Mogul (E39)
Bulb Finish	Clear
Rated Life	20000V/15000H hours
Operating Position	Universal

# **ELECTRICAL**

ded	Lamp Watts	400
	Lamp Oper. Voltage (Nom.)	135
	CLICTAINADILITY	

#### SUSTAINABILITY

Recycling Program

### **NOTES**

# **PHOTOMETRIC**


Initial Lumens	36000V/32000H	
Lumens Per Watt	90	
Scotopic Lumens (S/P 1.7)	61200	
Lamp Lumen Depreciation (LLD)	.65 (65%) @ 8000 hours	
Correlated Color Temperature	4200K	
Chromaticity Coordinates (CIE-x,y).380 .377		
Color Rendering Index (CRI)	65	

# **PHYSICAL**


Bulb Diameter	4.625" (120mm)
Max. Overall Length (MOL)	11.5" (292mm)
Light Center Length (LCL)	7.0" (178mm)
Effective Arc Length	39 mm
Max. Base Temperature (°C)	210
Max. Bulb Temperature (°C)	450
Socket Pulse Rating (KV)	-
Luminaire Type	Enclosed Rated




**ED37** 



Dia. = 4.625" (120mm) MOL = 11.5" (292mm) LCL = 7.0" (178mm) Base = Mogul (E39)





THIS LAMP CONFORMS TO FEDERAL STANDARD 21 CFR 1040.30

**Warning:** This lamp can cause skin burn and eye inflammation from shortwave ultraviolet radiation if outer envelope of the lamp is broken or punctured. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Lamps that will automatically extinguish when outer envelope is broken or punctured are commercially available.