

POWERSTRIKE™ PULSE START METAL HALIDE LAMPS

Uniform Technology
High Efficiency, Long Life
Enclosed Fixtures

HIGH INTENSITY DISCHARGE LAMPS

Watts	Bulb	Item#	Description	ANSI	Lumens		Dimensions		Avg. Life (Hours)	Color		Case		
					Initial (lm)	Mean (lm)	MOL (in)	LCL (in)		Temp (K)	CRI	Finish	Qty.	Manufacture Production Code
Powerstrike™ Pulse Start Metal Halide Lamps - Mogul Screw Base														
400	ED28	1589	MS400/ED28/PS/U/4K	M155/E,M135/E	39000	27000	8.31	5.00	20000	4200	65	Clear	12	N04009181402
*400	ED28	1624	MS400/ED28/C/PS/U/4K	M155/E,M135/E	37000	25700	8.31	5.00	20000	4000	70	Coated	12	N04009182402
400	ED28	1590	MS400/ED28/PS/BU/4K	M155/E,M135/E	44000	35000	8.31	5.00	20000	4200	65	Clear	12	N04009181412
*400	ED28	1591	MS400/ED28/C/PS/BU/4K	M155/E,M135/E	42000	33000	8.31	5.00	20000	4000	70	Coated	12	N04009182412
400	ED28	1547	MS400/ED28/PS/N/4K	M155/E,M135/E	44000	35000	8.31	5.00	20000	4200	65	Clear	12	N04009181422
*400	ED28	1548	MS400/ED28/C/PS/N/4K	M155/E,M135/E	42000	33000	8.31	5.00	20000	4000	70	Coated	12	N04009182422
400	ED28	1552	MS400/ED28/PS/H75/4K	M155/E,M135/E	39000	31000	8.31	5.00	20000	4200	65	Clear	12	N04009181432
*400	ED28	1553	MS400/ED28/C/PS/H75/4K	M155/E,M135/E	39000	31000	8.31	5.00	20000	4000	70	Coated	12	N04009182432
400	ED37	1592	MS400/ED37/PS/U/4K	M155/E,M135/E	39000	27000	11.50	7.00	20000	4200	65	Clear	12	N04009171402
400	ED37	1593	MS400/ED37/PS/BU/4K	M155/E,M135/E	42000	31000	11.50	7.00	20000	4200	65	Clear	12	N04009171412
*400	ED37	1594	MS400/ED37/C/PS/BU/4K	M155/E,M135/E	42000	29000	11.50	7.00	20000	4000	70	Coated	12	N04009172412
400	ED37	1549	MS400/ED37/PS/N/4K	M155/E,M135/E	42000	31000	11.50	7.00	20000	4200	65	Clear	12	N04009171422
*400	ED37	1625	MS400/ED37/C/PS/N/4K	M155/E,M135/E	42000	29000	11.50	7.00	20000	4000	70	Coated	12	N04009172422
400	ED37	1551	MS400/ED37/PS/H75/4K	M155/E,M135/E	42000	29000	11.50	7.00	20000	4200	65	Clear	12	N04009171432
*400	ED37	1550	MS400/ED37/C/PS/H75/4K	M155/E,M135/E	39000	31000	11.50	7.00	20000	4000	70	Coated	12	N04009172432
*400	T15	1653	MS400/T15/PS/H75/4K	M155/E,M135/E	39000	31000	11.50	7.00	20000	4200	65	Clear	24	N04009351402
450	ED37	1626	MS450/ED37/PS/N/4K	M144/E	50000	40000	11.50	7.00	20000	4000	68	Clear	12	N04509171402
450	ED37	1627	MS450/ED37/C/PS/N/4K	M144/E	47000	37000	11.50	7.00	20000	3700	70	Coated	12	N04509171402
750	BT37	1508	MS750/BT37/PS/HBU/4K	M149/E	80000	60000	11.50	7.00	16000	4200	65	Clear	12	N07509271402
*750	BT37	1638	MS750/BT37/C/PS/HBU/4K	M149/E	75000	56000	11.50	7.00	16000	4000	70	Coated	12	N07509272402
875	BT37	1628	MS875/BT37/PS/BU/4K	M166/E	100000	80000	11.50	7.00	20000	4000	68	Clear	12	N08759271402
875	BT37	1629	MS875/BT37/PS/BD/4K	M166/E	100000	80000	11.50	7.00	20000	4000	68	Clear	12	N08759271412
875	BT37	1630	MS875/BT37/PS/HOR/4K	M166/E	95000	76000	11.50	7.00	12000	4000	68	Clear	12	N08759271422
1000	BT37	1509	MS1000/BT37/PS/U/4K	M141/E	110000	96000	11.50	7.00	15000	4200	65	Clear	12	N10009271402
*1000	BT56	1639	MS1000/BT56/PS/BU/4K	M141/E	110000	86000	15.38	9.50	10000+	4200	65	Clear	6	N10009261402
*1000	BT56	1640	MS1000/BT56/C/PS/BU/4K	M141/E	105000	80000	15.38	9.50	10000+	4000	70	Coated	6	N10009262402

* Items only available for special orders

All measurements are shown in inches unless noted

Manage in Accordance with Disposal Laws

See www.htr-group.com or 1-888-537-4874

See page 18/19/20 for safety handling and warning purposes

