



SAT IMAGE overlay




Scale: as noted

Date: 06/19/09

Drawn By: mjl

This information is confidential and the sole property of RAB Lighting. It is not to be reproduced or distributed to others without the written permission of RAB Lighting. The calculation and results thereof as shown in this report are based on information provided by the customer. Therefore design parameters such as surface reflectances, size, mounting height, depreciation factors, orientation and tilt must be verified. RAB Lighting disclaims all implied warranties with regard to actual installed light levels as compared to those based on inaccurate or incomplete data. RAB LIGHTING NEITHER WARRANTIES OR REPRESENTS THE APPROPRIATENESS, COMPLETENESS OR SUITABILITY OF DESIGN ILLUSTRATION FOR SATISFYING ANY APPLICABLE REGULATORY CODE REQUIREMENTS. NOT FOR CONSTRUCTION.



Scale: as noted

Date: 06/19/09

Drawn By: mjlw

This information is confidential and the sole property of RAB Lighting. It is not to be reproduced or distributed to others without the written permission of RAB Lighting. The calculation and results thereof as shown in this report are based on information provided by the customer. Therefore design parameters such as surface reflectances, size, mounting height, depreciation factors, orientation and tilt must be verified. RAB Lighting disclaims all implied warranties with regard to actual installed light levels as compared to those based on inaccurate or incomplete data. RAB LIGHTING NEITHER WARRANTIES OR REPRESENTS THE APPROPRIATENESS, COMPLETENESS OR SUITABILITY OF DESIGN ILLUSTRATION FOR SATISFYING ANY APPLICABLE REGULATORY CODE REQUIREMENTS. NOT FOR CONSTRUCTION.




Image - Design Visualization LED



Scale: as noted

Date: 06/19/09

Drawn By: mjlw

This information is confidential and the sole property of RAB Lighting. It is not to be reproduced or distributed to others without the written permission of RAB Lighting. The calculation and results thereof as shown in this report are based on information provided by the customer. Therefore design parameters such as surface reflectances, size, mounting height, depreciation factors, orientation and tilt must be verified. RAB Lighting disclaims all implied warranties with regard to actual installed light levels as compared to those based on inaccurate or incomplete data. RAB LIGHTING NEITHER WARRANTIES OR REPRESENTS THE APPROPRIATENESS, COMPLETENESS OR SUITABILITY OF DESIGN ILLUSTRATION FOR SATISFYING ANY APPLICABLE REGULATORY CODE REQUIREMENTS. NOT FOR CONSTRUCTION.

Energy Saving Analysis for:

Project:

Prepared: November 1, 2010

Contact: 0

Tel: -

Email: [0](#)

Over 5 Years You will Save in

Proposal A

Proposal B

\$ 13,337

Energy Costs


See details below...

Project Assumptions

Square Feet Area	
Cost per kWh	\$ 0.15
Daily Operating Hrs	10 Hrs
Days/Year	365
Annual Operating Hrs	3,650 Hrs

Input
Output

Period Energy Saving



	Existing	Proposal A	Proposal B
Fixture Catalog #	400w MH Area	ALED20	
Description	400w MH Area	22w LED Area	
Input Watts/ Fixture	450	22	
Quantity	12	24	
Total System Watts	5,400	528	
Total Load kW	5.4 kW	0.5 kW	
Annual kWh	19,710 kWh	1,927 kWh	
Annual Energy Cost	\$ 2,957	\$ 289	
Monthly Energy Cost	\$ 246	\$ 24	
Per Fixture Cost		\$ 422	\$ -
Total Equipment Cost		\$ 10,128	
Install Labor & Materials		\$ 3,600	
Annual Cost of Sys Maintenance	\$ 239	\$ -	
Annual Lamp Disposal Charges	\$ -	\$ -	
Rebate \$\$ per Fixture		\$ 120	\$ -
Total Project Rebate		- \$ 2,880	
Total Cost of Ownership 5 yrs	15,976	12,293	

Energy Savings & Payback Analysis

Watts/ Square Foot			
Annual Energy Savings		\$ 2,667	
Energy Saving Over 5 yrs		\$ 13,337	
Monthly Energy Cost for Waiting		\$ 222	
Annual Operating Savings		\$ 2,906	
Years to Payback		3.73 yrs	
Your Rate of Return IRR	5% Annual Rate of Inflation	14%	
Period of Evaluation		5 yrs	5 yrs

Savings estimates are based on assumptions subject to change. Actual savings may vary.



ALED20



JOB NAME: _____
 DATE: _____
 TYPE: _____

DESCRIPTION

LED Area Lights

SPECIFICATIONS

Color Uniformity:

RAB's range of CCT (Correlated color temperature) follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI

Finish:

C78.377-2008.
 Chip and fade resistant polyester powder coat finish.

Gaskets:

High temperature silicone.

Green Technology:

RC LEDs are Mercury and UV free.

Housing:

Precision die cast aluminum housing, lens frame and mounting plate.

IESNA LM-79 & IESNA LM-80 Testing:

RAB LED luminaires have been tested by an independent laboratory in accordance with IESNA LM-79 and 80, and have received the Department of Energy "Lighting Facts" label.

Lumen Maintenance:

The LED will deliver 70% of its initial lumens at 50,000 hours of operation.

UL Listing:

Suitable for wet locations. Suitable for mounting within 4' of the ground.

Warranty:

RAB LED fixtures give you peace of mind because both the fixture and light engine components are backed by RAB's 5 Year Warranty. For more information,

Ambient Temperature:

Suitable for use in 50C (122F) ambient temperatures

Cold Weather Starting:

The minimum starting temperature is -30°C

Color Accuracy:

70 CRI

Dark Sky Approved:

The International Dark Sky Association has approved this product as a full cutoff, fully shielded luminaire.

Driver:

Automatic Voltage Sensing Driver for 120 – 277 volts

EPA:

0.10

Fixture Efficacy:

63 Lumens per Watt

For use on LEED Buildings:

IDA Dark Sky Approval means that this fixture can be used to achieve LEED Credits for Light Pollution Reduction.

Heatsink:

Integral cast aluminum mounting pad and external fins for optimal heat sinking to ensure cool operation with maximum LED life and light output.

LED Light Engine:

Two Multi-chip 10W high output long life LED Driver: Constant Current, Class 2

Light Color:

5584 K (Daylight)

Patents:

The ALED20 design is protected under patents pending in Canada, U.S., China, Taiwan and Mexico.

Total Harmonic Distortion:

THD = 8.4%


Color:

Bronze

Weight:

5.1

DIMENSIONS



ORDERING INFORMATION

LED Lamp supplied with fixture	Total Watts	Lamp Type	Lamp Base	Ballast	Starting Amps/ Operating Amps				Input Watts	LAMP ANSI	Initial Lumens	Lamp Hours
					120V	208V	240V	277V				
	20	L.E.D.	Thermal Heatsink	Constant Current	0.5	0.5	0.5	0.125	22	N/A	1401	50000
Factory Installed Options Add suffix to Catalog Number				Photocontrol for 277V (/PC2)								Photocontrol for 120V (/PC)

Note: Specifications may change without notice



PS4-11-20D2

JOB NAME: _____

DATE: _____

TYPE: _____

DESCRIPTION

Square steel poles drilled for 2 Area Lights at 180°. Designed for ground mouting. Poles are stocked nationwide for quick shipment. Protective packaging ensures poles arrive at the job site good as new.

SPECIFICATIONS

Base Plates:

Slotted base plates 36,000 p.s.i.

Color:

Bronze

Hand Holes:

Reinforced with grounding lug and removable cover.

Shaft:

46,000 p.s.i. minimum yield

Shipping Protection:

All poles are shipped in individual corrugated cartons to prevent finish damage.

Anchor Bolt Templates:

WARNING: Template must be printed on 11" x 17" sheet for actual size. CHECK SCALE BEFORE USING. Templates shipped with anchor bolts and available

Anchor Bolt:

3/4" x 17" x 3" Galvanized anchor bolts and galvanized hardware and anchor bolt template. All bolts have a 3" hook

Base Dimension:

8"

Bolt Circle:

8-9"

Gauge:

11

Hand Hole Dimensions:

3" x 5"

Height:

20 FT

MaxEPA's/Max Weights:

70MPH: 8.3 ft²/240 lb

80MPH: 5.6 ft²/165 lb

90MPH: 3.6 ft²/110 lb

100MPH: 2.2 ft²/75 lb

110MPH: 1.0 ft²/45 lb

120MPH: 0.2 ft²/20 lb

Pre-Shipped Anchor Bolts:

Bolts can be pre-shipped upon request for additional freight charge

Shaft Size:

4"

Terms of Sale:

Pole Terms of Sale is available

Wall Thickness:

1/8"

Weight:

137

DIMENSIONS

