# BLED2X5-36W

Professional Grade LED Bollards compliment any pathway or landscape design. Low profile 5W Square LED comes in Cool, Warm and Neutral color temperatures. Bollards come in 18, 36 and 42" versions

### **LED Info Driver Info**

Watts:	5W	Type:	Constant Current
Color Temp:	5000K (Cool)	120V:	0.2 A
Color Accuracy:	68	208V:	0.12 A
L70 Lifespan:	100000	240V:	0.1 A
LM79 Lumens:	392	277V:	N/A
Efficacy:	37 LPW	Input Watts:	11W
		Efficiency:	47%

# **Technical Specifications**

### **UL Listing:**

Suitable for wet locations. Suitable for mounting within 4' of the ground.

### **Lumen Maintenance:**

The LED will deliver 70% of its initial lumens at 100,000 hours of operation.

### Driver:

Multi-chip 2x5W high output long life LED Driver Constant Current, Class II, 120V-240V, 50/60 Hz, 400mA

### **Color Temperature (Nominal CCT):**

5000K

### **Color Accuracy:**

68 CRI

### **Thermal Management:**

Cast aluminum Thermal Management system for optimal heat sinking. The BLED is designed for cool operation, most efficient output and maximum LED life by minimizing LED junction temperature.

### **Housing:**

Precision die cast aluminum housing, lens frame.

# Mounting:

36" Bollard

### Gaskets:

High temperature silicone.

Chip and fade resistant polyester powder coat finish.


### **Green Technology:**

BLEDs are Mercury, Arsenic and UV free.

Copyright ©2012 RAB Lighting, Inc. All Rights Reserved



Weight: 12.3 lbs



## IESNA LM-79 & IESNA LM-80 Testing:

RAB LED luminaires have been tested by an independent laboratory in accordance with IESNA LM-79 and 80, and have received the Department of Energy "Lighting Facts" label.

### **Color Stability:**

RAB LEDs exceed industry standards for chromatic stability.

# **Color Uniformity:**

RAB's range of CCT (Correlated color temperature) follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2008.

### Warranty:

RAB LED fixtures give you peace of mind because both the fixture and driver components are backed by RAB's 5 Year Warranty. For more information,

# **Country of Origin:**

Designed by RAB in New Jersey and assembled in the USA by RAB's IBEW Local 3 workers.

### **Buy American Act Compliant:**

This product is a COTS item manufactured in the United States, and is compliant with the Buy American Act.

### **Recovery Act (ARRA) Compliant:**

This product complies with the 52.225-21 "Required Use of American Iron, Steel, and Manufactured Goods--Buy American Act-- Construction Materials (October 2010)

### **Trade Agreements Act Compliant:**

This product is a COTS item manufactured in the United States, and is compliant with the Trade Agreements Act.

Page 1 of 2



Email: sales@rabweb.com Note: Specifications are subject to change without notice

# **GSA Schedule:**

Suitable in accordance with FAR Subpart 25.4

