
DLED6R12YY

LED retrofit downlights are perfect for updating existing recessed

lighting without changing the fixture. Equivalent to 65W Par.



Color: White



Weight: 0.0 lbs

LED Info Driver Info

Watts:	12W	Type:	Constant Current
Color Temp:	2700K	120V:	0.11A
Color Accuracy:	84	208V:	N/A
L70 Lifespan:	100000	240V:	N/A
LM79 Lumens:	675	277V:	N/A
Efficacy:	53 LPW	Input Watts:	13W
		Efficiency:	94%

Technical Specifications

UL Listed:

Suitable for damp locations.

ENERGY STAR®:

This product is ENERGY STAR® qualified.

Compatibility:

Low-profile design for maximum compatibility with many 5" and 6" incandescent recessed downlight housings. See housing compatibility.

Lumen Maintenance:

100,000-hour LED lifespan based on IES LM-80 results and TM-21 calculations.

LEDs:

High-output, long-life LEDs with 3 step binnning and integrated driver technology.

Driver:

Innovative integrated driver technology with 120V TRIAC and ELV dimming. See compatibility guide .

Lens:

Polycarbonate diffusion lens for smooth light output.

Surge Protection:

2.5kv.

Color Consistency:

3-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color.

Housing:

Professional-grade, die-cast aluminum construction.

Edison E26 medium base adapter included. GU24 socket adapter sold separately.

Installation:

Pre-installed Torsion springs and optional friction clips are both included to aid in attaching and securing the 6" DLED to the incandescent housing.

Correlated Color Temp. (Nominal CCT):

2700K Residential Warm.

Fixture Efficacy:

53 Lumens per Watt.

Color Accuracy (CRI):

84 CRI.

Equivalency:

12W replaces 65W Par.

Finish:

Chip and fade resistant polyester powder coat finish.

IESNA LM-79 & LM-80 Testing:

RAB LED luminaires have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80, and have received the Department of Energy "Lighting Facts" label.

California Title 24:

DLED Retrofit Downlight complies with California Title 24 building and electrical codes.

Green Technology:

Mercury and UV free, and RoHS compliant.

Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. See our full warranty.



Email: sales@rabweb.com On the web at: www.rabweb.com Note: Specifications are subject to change without notice