

HBLED10A

Bullet shape die cast aluminum flood with 10 watt LED Light Engine. Equivalent to 60W PAR Halogen. Comes with flood reflector installed. Optional spot reflector included for field installation.

Color: Bronze

Weight: 3.5 lbs



LED Info

Watts: 10W
 Color Temp: 5200K (Cool)
 Color Accuracy: 61
 L70 Lifespan: 100000
 LM79 Lumens: 338
 Efficacy: 25 LPW

Driver Info

Type: Constant Current
 120V: 0.21 A
 208V: 0.14 A
 240V: 0.12 A
 277V: N/A
 Input Watts: 13W
 Efficiency: 75%

Technical Specifications

UL Listing:

Suitable for wet locations. Suitable for mounting within 4' of the ground.

Lumen Maintenance:

The LED will deliver 70% of its initial lumens at 100,000 hours of operation.

Thermal Management:

Cast aluminum patent pending Thermal Management system for optimal heat sinking. The LFLOOD is designed for cool operation, most efficient output and maximum LED life by minimizing LED junction temperature.

Swivels:

Fully adjustable with sure-grip locks. 1/2" NPS threaded arm with serrated locking swivel fits all standard mounting covers. Color matched EZ Grip lock nuts. Stainless steel screw.

Housing:

Precision die cast aluminum housing

Gaskets:

High Temperature Silicone

Finish:

Chip and fade resistant polyester powder coat finish.

Warranty:

RAB LED fixtures give you peace of mind because both the fixture and driver components are backed by RAB's 5 Year Warranty. For more information,

Green Technology:

RAB LEDs are Mercury, Arsenic and UV free.

California Title 24:

LFLOOD complies with California Title 24 building and electrical codes.

IESNA LM-79 & IESNA LM-80 Testing:

RAB LED luminaires have been tested by an independent laboratory in accordance with IESNA LM-79 and 80, and have received the Department of Energy "Lighting Facts" label.

Color Stability:

RAB LEDs exceed industry standards for chromatic stability.

Color Uniformity:

RAB's range of CCT (Correlated color temperature) follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2008.

Cold Weather Starting:

The minimum starting temperature is -40°F/-40°C

Reflectors:

NEMA 5x5 floodlight reflector with 4x4 optional spotlight reflector for field installation. Photometrics show flood configuration

LFLOOD 10W:

LED Floodlight that reduces energy consumption by 70% compared to 60W PAR38. Spot and Flood beam patterns. Recommended for Residential and Commercial applications.

Color Temperature:

5200K



HBLED10A - continued

Color Accuracy:

61 CRI

Driver:

Multi-chip 10W high output long life LED Driver
Constant Current, Class II, 120V-240V, 50/60 Hz,
350mA

Surge Protection:

1KV

Patents:

LFLOOD thermal Management technology is protected
under utility patents pending in the U.S., Canada and
China.

Equivalency:

The HBLED10 is Equivalent in delivered lumens to a
45W PAR Floodlight.

HID Replacement Range:

The HBLED10 can be used to replace 45-75W PAR
Floodlights based on delivered lumens.

Country of Origin:

Designed by RAB in New Jersey and assembled in
Taiwan

Trade Agreements Act Compliant:

This product is a product of Taiwan and a "designated
country" end product that complies with the Trade
Agreements Act.

GSA Schedule:

Suitable in accordance with FAR Subpart 25.4

